

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## EYS46SA 1-1/4" Alu Cond Seal Crouse-Hinds

Catalog Number	EYS46SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eys Conduit Sealing Fitting, Male and
	Female, Copper-Free Aluminum, Vertical or Horizontal, 1-1/4"
Weight per unit	
Product Category	Aluminum
eatures	
connection	Male Threaded, Female Threaded
dimensions	2.1900 IN X 2.1900 IN X 5.0600 IN
Descriptions	
Description	1-1/4" ALU COND SEAL
extra long description	CRS-H EYS46 SA 1 1/4 NPT MALE/FEM A
Features	Crouse-Hinds series EYS and EZS explosionproof sealing fittings
	restrict the passage of gases, vapors or flames from one portion
	of the electrical installation to another, limit explosions to the
	sealed off enclosure, and limit pre-compression or "pressure
	piling" in conduit systems. EYS sealing fittings are available for
	installation in either vertical only or in both horizontal or vertica
	positions. They are available in a variety of materials, including
	Feraloy iron alloy and/or ductile iron, copper-
Long Description	Eaton Crouse-Hinds series EYS conduit sealing fitting, Male and
	female, Copper-free aluminum, Vertical or horizontal, 1-1/4"
Product Type	
Special Features	Horizontal/Vertical Position
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274379210
Manufacturers Part Number	EYS46 SA
UPC	782274379210
Γaxonomies, Classifications, and (	Categories
Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting
Packaging	
Carton	
Package	
Weight Per each	1.15



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	CLASS I DIV 1 2 GROUP C D, CLASS II DIV 1 2 GROUP E F G, CLASS
	III
standard	UL 886, CSA C22.2