



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



FAZC503NA Faz-Na UI 489 MCB 240VAC 3P 50A C Curve

Eaton Corp

Catalog Number	FAZC503NA
Manufacturer	Eaton Corp
Description	Eaton Faz Branch Protector, UI 489 Industrial Miniature Circuit Breaker - Supplementary Protector, Medium Levels Of Inrush Current Are Expected, 50 A, 10 Kaic, Three-Pole, 240 V, 5-10X /N, 50-60 HZ, Screw Terminals, C Curve
Weight per unit	0.8900 (lbs/each)
Product Category	3 Pole

Features

dimensions	2.1000 IN X 4.1000 IN X 3.0000 IN
interrupt rating	10
Poles	3
Voltage Rating	277/480V

Descriptions

Description	FAZ-NA UL 489 MCB 240VAC 3P 50A C CURVE
extra long description	ETN FAZ-C50/3-NA FAZ-NA UL 489 MCB
Features	Eaton's FAZ, dual rated UL and IEC circuit breakers are ideal for providing protection in many applications. A current limiting design provides fast short-circuit interruption, offering superior protection by reducing peak let-through current. Superior product quality, tested reliability and safety make Eaton's UL 1053 Residual Current Circuit Breaker (RCCB) the optimum product for residual current applications. The UL 1053 RCCB circuit breakers provide safety and protection for personnel and equipment.
Long Description	Eaton FAZ branch protector, UL 489 Industrial miniature circuit breaker - supplementary protector, Medium levels of inrush current are expected, 50 A, 10 kAIC, Three-pole, 240 V, 5-10X /n, 50-60 Hz, Screw terminals, C Curve
Product Type	Faz-Na UI 489 MCB 240VAC 3P 50A C Curve

Manufacturer Information

Brand	Eaton Corp
GTIN	00786689240813
Manufacturers Part Number	FAZ-C50/3-NA
UPC	786689240813

Taxonomies, Classifications, and Categories

Category Description	MOLDED CASE BREAKERS
Type	Branch protector



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton 1

Weight Per each 0.89

Uses, Certifications, and Standards

Application Datacenters - IT Space: CI and Hyper Converged
and Equipment - Marine Vessels and Equipment -
OtherOtherGeneration - Renewable Energy - Alternative
EnergyGeneration - Conventional Energy - Conventional Energy

standard UL 489