

ELLIOT ELECTRIC SUPPLY Mar Deliver Lower Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FD32 2G FD Box Crouse-Hinds

Catalog Number	FD32
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FD Device Box, Deep, Feralo Iron Alloy, Two-Gang, 1"
Weight per unit	
Product Category	
atures	
Cable Entry	(1) End
dimensions	4.1900 IN X 2.6900 IN X 5.3100 IN
Material	Electrogalvanized With Aluminum Acrylic Painted Feraloy Iron Alloy
mensions and Weight	
Size	1 in
escriptions	
Description	2G FD BOX
extra long description	CRS-H FD32 1 NPT DE CST IRON FD BX
Features	Crouse-Hinds series FS and FD device boxes are installed in non-hazardous area conduit systems to accommodate wiring devices, act as pull boxes or provide openings for taps and splices. They are suitable for use in wet locations when used with gasketed covers. FS and FD device boxes are available in two box depths with a wide variety of gang configurations, hub configurations and hub sizes. They are manufactured in cast iron, aluminum, stainless steel and malleable iron. Malleable iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FD device box, Deep, Feralo iron alloy, Two-gang, 1"
Product Type	1 NPT De CST Iron FD BX Two GNG MTG Lugs
Special Features	Configuration Type FD, With Mounting Lug, Dimension 4-5/8 In Width X 2-11/16 In Depth X 5-3/16 In Height
anufacturer Information	
Brand	Eaton
GTIN	00782274397405
Manufacturers Part Number	FD32
UPC	782274397405



We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Туре	DEVICE BOX
Packaging	
Carton	1
Weight Per each	4.25
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	SURFACE
standard	UL 514, CSA C22.2, Federal Specification W-C-5860