




GE
Lighting

66666 - FLE26/2DMR40/BX

GE energy smart® dimming CFL 26 watt R40 floodlight 1-pack

- \$56 in energy savings over the life of the bulb based on 3 hours per day usage
- Energy Star Qualified
- Estimated yearly energy costs \$3.13 based on 3 hours per day \$0.11 per kWh
- Lasts 7.3 years based on 3 hours per day usage
- R40 indoor floodlight with medium base for use in directional fixtures such as recessed can lighting
- The GE energy smart® indoor floodlight CFLs feature a GE Spiral® bulb on the inside that uses 75% less energy and lasts up to 5 times longer than incandescent indoor reflectors. These bulbs' funnel shape help direct light where it is needed better than a standard CFL or incandescent bulb. Use GE energy smart® indoor floodlight CFLs in indoor recessed track and recessed fixtures to create broad beams of light in any room or space
- 90 watt replacement uses only 26 watts



GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	R40
Base	Medium Screw (E26)
Bulb Finish	Soft white
Equivalent Wattage (NOM)	100.0 W
Rated Life (NOM)	8000.0 h
Bulb Material	Soft glass
Dimming Capability	Yes
Additional Info	GE energy smart® CFL R40 90W replacement
Primary Application	Turn Signal, Front

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1300.0
Nominal Initial Lumens per Watt (NOM)	50.0
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	26.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	6.700 in(170.2 mm)
Bulb Diameter (DIA) (NOM)	5.000 in(127.0 mm)

PRODUCT INFORMATION

Product Code	66666
Description	FLE26/2DMR40/BX
Standard Package	Case
Standard Package GTIN	10043168666661
Standard Package Quantity	1
Sales Unit	Layer
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	3
UPC	43168666664




GE
Lighting

66666 - FLE26/2DMR40/BX

GE energy smart® dimming CFL 26 watt R40 floodlight 1-pack

- \$56 in energy savings over the life of the bulb based on 3 hours per day usage
- Energy Star Qualified
- Estimated yearly energy costs \$3.13 based on 3 hours per day \$0.11 per kWh
- Lasts 7.3 years based on 3 hours per day usage
- R40 indoor floodlight with medium base for use in directional fixtures such as recessed can lighting
- The GE energy smart® indoor floodlight CFLs feature a GE Spiral® bulb on the inside that uses 75% less energy and lasts up to 5 times longer than incandescent indoor reflectors. These bulbs' funnel shape help direct light where it is needed better than a standard CFL or incandescent bulb. Use GE energy smart® indoor floodlight CFLs in indoor recessed track and recessed fixtures to create broad beams of light in any room or space
- 90 watt replacement uses only 26 watts



GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Self-Ballasted
Bulb	R40
Base	Medium Screw (E26)
Bulb Finish	Soft white
Equivalent Wattage (NOM)	100.0 W
Rated Life (NOM)	8000.0 h
Bulb Material	Soft glass
Dimming Capability	Yes
Additional Info	GE energy smart® CFL R40 90W replacement
Primary Application	Turn Signal, Front

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	1300.0
Nominal Initial Lumens per Watt (NOM)	50.0
Color Temperature (NOM)	2700.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	26.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	6.700 in(170.2 mm)
Bulb Diameter (DIA) (NOM)	5.000 in(127.0 mm)

PRODUCT INFORMATION

Product Code	66666
Description	FLE26/2DMR40/BX
Standard Package	Case
Standard Package GTIN	10043168666661
Standard Package Quantity	1
Sales Unit	Layer
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	3
UPC	43168666664