

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRSR350 Fusetron Dual Element Fuse Class RK5 Bussmann Fuses

Catalog Number	
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK5 Fuse, FRS-R, Time-Delay,
	Dual-Element, Current Limiting Fuse, 350 A, Non-Indicating Fuse, Interrupting Rating Of 200 Ka At 600 Vac and 20 Ka At 300 VDC
Walabt par upit	
Weight per unit	
Product Category	Duai ciement
Features	
amperage rating	
connection	
dimensions	
element	
Fuse Class	Class RK5
interrupt rating	20 kAIC at 300 Vdc200 kAIC at 600 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	2.34 In Diameter X 11.63 In Length
Descriptions	
Description	FUSETRON DUAL ELEMENT FUSE CLASS RK5
extra long description	BUSS FRS-R-350 FUSETRON DUAL ELEMEN
Features	Bussmann's UL Class RK5 Fusetron product offering provides
	energy efficient advanced protection with its dual-element,
	time-delay construction and is available with optional open fuse
	indication on select ratings. Available in both 250Vac and
	600Vac, 200kA RMS Sym interrupting rating and sizes ranging
	from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of
	time-delay at 500 of rated current (8 seconds for 1/10-30A sizes).
Long Description	Eaton Bussmann Series Class RK5 fuse, FRS-R, time-delay,
	dual-element, current limiting fuse, 350 A, non-indicating fuse,
	interrupting rating of 200 kA at 600 Vac and 20 kA at 300 Vdc
Product Type	Fusetron Dual Element Fuse Class RK5
Special Features	Renewable



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712508520
Manufacturers Part Number	FRS-R-350
UPC	051712508520
Taxonomies, Classifications, and C	ategories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	1
Weight Per each	2.34
Uses, Certifications, and Standards	5
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked