

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FSC32 2G FSC-Box Crouse-Hinds

Catalog Number	FSC32
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet FS Device Box, Shallow,
	Feraloy Iron Alloy, Two-Gang, C Shape, 1"
Weight per unit	3.6 (lbs/each)
Product Category	FS & FD Type Boxes & Covers
eatures	
Cable Entry	(1) Each End
dimensions	
Material	Natural Finished Sand Copper-Free Aluminum
Dimensions and Weight	
Size	1 in
Descriptions	
Description	2G FSC-BOX
extra long description	CRS-H FSC32 1 FS/FD TWO GANG CASE D
Features	Crouse-Hinds series FS and FD device boxes are installed in
	non-hazardous area conduit systems to accommodate wiring
	devices, act as pull boxes or provide openings for taps and
	splices. They are suitable for use in wet locations when used
	with gasketed covers. FS and FD device boxes are available in
	two box depths with a wide variety of gang configurations, hub
	configurations and hub sizes. They are manufactured in cast
	iron, aluminum, stainless steel and malleable iron. Malleable
	iron boxes are also a
Long Description	Eaton Crouse-Hinds series Condulet FS device box, Shallow,
	Feraloy iron alloy, Two-gang, C shape, 1"
Product Type	1 FS/FD Two Gang Case Device BX
Special Features	Configuration Type FSC, With Ground Screw, Dimension 2-3/4 In
	Width X 1-7/8 In Depth X 6-9/32 In Height
Vanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274411507
Manufacturers Part Number	FSC32
UPC	782274411507
axonomies, Classifications, and C	Categories
Category Description	
Туре	DEVICE BOX



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	1
Weight Per each	3.5999
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Mounting	FLUSH
standard	UL 514, ANSI C33.84, CSA C22.2, Federal Specification W-C-5860