



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



FSKWRD 3W-2P RCPT CVR *Appleton/Oz Gedney*

Catalog Number	FSKWRD
Manufacturer	Appleton/Oz Gedney
Description	Duplex Receptacle Cover, Material: Diecast Copperfree (4/10 Of 1 PCT) Aluminum, Size: 1-3/8 In Opening, Number Of Outlet: 2, Mounting: Box, Length: 3.16 In, Width: 4.56 In, For Use With Non-Locking Blade Plugs
Weight per unit	0.5000 (lbs/each)
Product Category	FS & FD Type Boxes & Covers

Features

Material	Diecast Copperfree (4/10 Of 1 PCT) Aluminum
number of outlet	2

Dimensions and Weight

Size	1-3/8 IN Opening
------	------------------

Descriptions

Description	3W-2P RCPT CVR
extra long description	APP FSK-WRD WET LOC COVER-DUPLEX RE
Long Description	Duplex Receptacle Cover, Material: Diecast Copperfree (4/10 Of 1 PCT) Aluminum, Size: 1-3/8 IN Opening, Number Of Outlet: 2, Mounting: Box, Length: 3.16 IN, Width: 4.56 IN, For Use With Non-Locking Blade Plugs
Product Type	Wet Loc Cover-Duplex Recept(A)
Special Features	Also permits adequate access to cover screws for easy attachment of cover to FS, FD or other device box;Covers open all the way, permitting easy plug insertion and withdrawal;Duplex units accommodate one receptacle and one toggle switch or any combination of the two;Large head cover screws are captivated;Single cover units accommodate NEMA configuration receptacles for locking or non-locking blade plugs, or toggle switches;Unique design of spring door hinge provides smooth action;Wet location

Manufacturer Information

Brand	Appleton
GTIN	00781381458344
Manufacturers Part Number	FSK-WRD
UPC	781381458344

Taxonomies, Classifications, and Categories

Category Description	FS BOXES AND COVERS
Type	Duplex Receptacle Cover



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	10
Weight Per each	0.5

Uses, Certifications, and Standards

Application	For Use With Non-Locking Blade Plugs
Mounting	BOX