

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### GBB12R 12A 250VAC/125VDC Vfa 1/4X1-1/4" Rohs Fuse Bussmann Fuses

Manufacturer Bussmann Fuses
Manuacture Dussinalii i uses
Description Eaton GBB Series Very Fast-Acting Fuse, 1A, 250 Vac, 125 VDC
Weight per unit 0.0100 (lbs/each)
Product Category Small Dimension Fuses

#### **Features**

amperage rating	12 A
connection	Ferrule End X Ferrule End
dimensions	1.2500 IN X 0.2500 IN X 0.2500 IN
interrupt rating	200 AIC at 250 Vac10 kAIC at 125 Vac/dc
Material	Nickel-plated brass end cap constructionCeramic tube
Response Time	2 min at 150%, 1 sec at 250%
type of indicators	Non-Indicating
Voltage Rating	250 VAC, 125 VDC

## **Dimensions and Weight**

Size 1/	4 In Diameter X 1-1/4 In Length

# **Descriptions**

12A 250VAC/125VDC VFA 1/4X1-1/4" ROHS FUSE
EFSE GBB-12-R GBB 12A BUSS FA 5-IN
Very fast-acting, ceramic tube 1/4" x 1-1/4" ferrule fuse designed to UL 248-14 for overcurrent protection of sensitive electronic circuits. Install into a Bussmann Series fuse holder, block, or fuse clip or purchase with available axial leads for thru-hole installation. Eaton's GBB very fast-acting, ceramic tube 1/4" x 1-1/4" ferrule fuses are designed to UL 248-14 for overcurrent protection of sensitive electronic circuits. Order in cartridge fuse format and install into a Bussmann Series fuse holder, b
Eaton GBB Series Very fast-acting fuse, 1A, 250 Vac, 125 Vdc
GBB 12A Buss Fa 5-In Box -R
Interrupt Rating 200 Amp at 250 Vac, 10000 Amp at 125 Vac/Vdc, Material Ceramic Tube, Nickel Plated Brass Endcap, ROHS Compliant

### **Manufacturer Information**

Brand	Eaton Bussmann series
GTIN	00051712549899
Manufacturers Part Number	GBB-12-R
UPC	051712549899



standard

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	GLASS FUSES (and ceramic)	
Туре	Very fast-acting fuse	
Packaging Carton		
Carton	5	
Weight Per each	0.01	
Uses, Certifications, and Standards		
Application	Ind Facilities & Factories - Facility: Safety and Security Systems	

RoHS Compliant,CE Marked