

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



GFTWRST20GY 20A Comm Self Test TRWR GFR Gray Hubbell Wiring Devices

04040	
Catalog Number	GFTWRST20GY
Manufacturer	Hubbell Wiring Devices
Description	Power Protection Devices, Receptacle, Self Test, Gfci, TRWR,
	Commercial Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R,
	Gray
Weight per unit	
Product Category	Gen Purpose Recept & Surge Pro
eatures	
amperage rating	20
connection	Terminal Screws
Number of Wires	3-Wire Grounding
pallet quantity	
Phase	1
Poles	2-Pole
Voltage Rating	125
Wattage	
Wire Size	
Dimensions and Weight	
Size	Standard Sized Product
Descriptions	20A COMM SELF TEST TRWR GFR GRAY
Description extra long description	HWDK GFTWRST20GY 20A COMM SELF TEST
Features	AUTOGUARD [®] Self Test Technology 1st introduced by Hubbell
reatures	over 10 years agoself test monitoring now required in 2015 UL
	943 GFCI Safety Standard Hubbell AUTOGUARD® GFCI
	receptacles continually test and monitor for "people protection
	capability" automatically. This patented safety feature includes
	disconnecting power to the receptacle if critical components are
	damaged and GFCI protection is lost. GFCI auto-monitoring is
	conducted continuously within every 30 seconds. Also, clear
	visual indicators are pro
Long Description	Power Protection Devices, Receptacle, Self Test, GFCI, TRWR,
	Commercial Grade, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R,
	Gray
Product Type	
Special Features	Self Test, Tamper and Weather Resistant



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00883778122668
Manufacturers Part Number	GFTWRST20GY
series	Heavy Duty
UPC	883778122668
Taxonomies, Classifications, and Categ	pories
	Commercial GFCI devices
Туре	Tamper-Resistant, Weather Resistant
Availability	
Status	Inactive
Packaging	
Carton	1
Package	10
Weight Per each	0.35
Uses, Certifications, and Standards	
Application	Commercial Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-20R
standard	Meets All NEC [®] Requirements