



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



GRSS3 1-In Ex-PRF Cond Body *Hubbell--Killark*

| | |
|------------------|---|
| Catalog Number | GRSS3 |
| Manufacturer | Hubbell--Killark |
| Description | 1" Aluminum GRSS Outlet Body, 7 Internal Hub Config |
| Weight per unit | 2.8 (lbs/each) |
| Product Category | Alum |

Features

| | |
|-------------|--|
| Cable Entry | 1" hub |
| Material | Aluminum, Copper Free (less than 4/10 of 1%) |

Material, Color, and Finish

| | |
|-------|------|
| Color | Gray |
|-------|------|

Dimensions and Weight

| | |
|--------|---------------------------|
| Length | 7.875 |
| Size | 7.875 in x 6 in x 4.25 in |
| Width | 6 |

Descriptions

| | |
|------------------------|--|
| Description | 1-IN EX-PRF COND BODY |
| extra long description | KLRK GRSS-3 OUTLET BODY, SQUARE 1" |
| Long Description | 1" Aluminum GRSS Outlet Body, 7 Internal Hub Config |
| Product Type | Outlet Body, Square 1" Al |
| Special Features | Internal hubs. Blank cover included (GRRBC). Compact design. Furnished with internal ground screw. Cast-in brackets on cover for use with breaker-bar tools. |

Manufacturer Information

| | |
|---------------------------|------------------|
| Brand | KILLARK |
| GTIN | 00783936230146 |
| Manufacturers Part Number | GRSS-3 |
| series | GR Outlet Bodies |
| UPC | 783936230146 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------------------|
| Category Description | HUB STYLE BOXES (GUAB, GUAT, ETC) |
| Type | Outlet Body With Cover |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 2.79 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Conduit boxes installed in conduit systems within hazardous areas to: protect conductors in threaded rigid conduit, act as pull and splice boxes, interconnect lengths of conduit, change conduit direction, and provide access to conductors for maintenance and future system changes.

standard

UL, CSA