

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Long Description

Special Features

Product Type

HBL8200I Dup RCPT, HG, 15A 125V, 5-15R, Iv Hubbell Wiring Devices

Catalog Number	HBL8200I
Manufacturer	Hubbell Wiring Devices
Description	Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Ivory.
Weight per unit	0.2500 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
eatures	
amperage rating	15
connection	Back and Side Wired Screw Terminals
Current Rating	15
Dielectric Strength	Withstands 2,000V minimum
Number of Wires	3-Wire
pallet quantity	3600
Phase	1
Poles	2 Dolo
Voltage Rating	125 V
Wattage	1875
Wire Size	#14 to #10
Dimensions and Weight	
Size	3.28 in x 1.65 in x 1.19 in
Descriptions	
Description	DUP RCPT, HG, 15A 125V, 5-15R, IV
extra long description	HWDK HBL8200I DUP RCPT, HG, 15A 125
Features	HBL® Extra Heavy Duty Max Hospital Grade Devices - UL
	requirements for Hospital Grade devices is more stringent than
	those for standard devices. Hubbell receptacles are designed to
	meet and exceed the standards with Exclusive nickel-plated
	bypass contact design increases contact pressure, lowering the
	operating temperature; Four point grounding system provides
	redundant grounding for low resistance ground continuity in high
	abuse areas; Impact resistant deep face design prevents
	breakage. Because of these

Self Grounding

Straight Blade Devices, Receptacles, Duplex, Hospital Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Ivory.

Dup RCPT, HG, 15A 125V, 5-15R, Iv



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	N	lanui	facturer I	Information
--	---	-------	------------	-------------

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585435626
Manufacturers Part Number	HBL8200I
series	Hospital Grade
UPC	783585435626

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	RECEPTACLE

Packaging

Carton	1	
Package	10	
Weight Per each	0.25	

Uses, Certifications, and Standards

Application	Extra Heavy Duty Hospital Grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-15R
standard	CSA Certified, C22.2, No. 42 File 285; Fed. Spec. W-C-596; NEMA®
	WD-6 Compliant; UL Listed to UL498 File No. E2186