

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBL8300HRED Dup RCPT, Com/HG, 20A 125V, 5-20R, RD Hubbell Wiring Devices

HBL8300HRED	
Hubbell Wiring Devices	
Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5- 20R, Red, Single Pack.	
0.0780 (lbs/each)	
Gen Purpose Recept & Surge Pro	
20	
Back and Side Wired Screw Terminals	
20	
Withstands 2,000V minimum	
Nylon	
3-Wire	
3600	
1	
2-Pole	
125 V	
2500	
#12 to #10	
3.28 in x 1.33 in x 1.05 in	



Descriptions

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Description	DUP RCPT, COM/HG, 20A 125V, 5-20R, RD		
extra long description	HWDK HBL8300HRED DUP RCPT, COM/HG,		
Features	HBL® Extra Heavy Duty Max Hospital Grade Devices - UL requirements for Hospital Grade devices is more stringent than those for standard devices. Hubbell receptacles are designed to meet and exceed the standards with Exclusive nickel-plated bypass contact design increases contact pressure, lowering the operating temperature; Four point grounding system provides redundant grounding for low resistance ground continuity in hig abuse areas; Impact resistant deep face design prevents breakage. Because of these		
Long Description	Straight Blade Devices, Receptacles, Duplex, Compact Hospital Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5- 20R, Red, Single Pack.		
Product Type	Dup RCPT, Com/HG, 20A 125V, 5-20R, RD		
Special Features	Standard Product		
Manufacturer Information			
Brand	WIRING DEVICE-KELLEMS		
GTIN	00783585247519		
Manufacturers Part Number	HBL8300HRED		

Taxonomies, Classifications, and Categories

Category Description	Industrial receptacles
Туре	Duplex Receptacle

Hospital Grade

783585247519

Packaging

series **UPC**

Carton	1	
Package	10	
Weight Per each	0.078	

Uses, Certifications, and Standards

Application	Hospital grade
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	5-20R
standard	CSA Certified, C22.2, No. 42 File 285; Fed. Spec. W-C-596; NEMA®
	WD-6 Compliant; UL Listed to UL498 File No. E2186