

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



HBLDS30 NM Sloped Disc, 30A Unfused, 4X *Hubbell Wiring Devices*

Catalog Number HBLDS30

Manufacturer Hubbell Wiring Devices

Description Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 30A 600V Ac, Screw Terminals, IP69K, Nema Type 4X, 12 Non-Metallic Sloped Top Enclosure, Culus, NSF, Ce, UI 508 / UI 60947-4-1a

Weight per unit 2.8 (lbs/each)

Product Category Distribution Equipment

Features

Shape Rounded Top

Material, Color, and Finish

Color Gray

Descriptions

Description	NM SLOPED DISC, 30A UNFUSED, 4X
extra long description	HWDK HBLDS30 NM SLOPED DISC, 30A UN
Features	NEC section 430.102(B) requires each motor controller to have a disconnect within line of sight from the motor and driven equipment. Hubbell's Circuit-Lock® Unfused Disconnect Switches are UL listed as a manual motor controller and also "suitable as a motor disconnect" and meet these code requirements.
Long Description	Industrial Grade, Motor Disconnect Switch, Unfused, 3 Pole, 30A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure, cULus, NSF, CE, UL 508 / UL 60947-4-1A
Product Type	NM Sloped Disc, 30A Unfused, 4X

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585763002
Manufacturers Part Number	HBLDS30
series	Non-Fused
UPC	783585763002

Taxonomies, Classifications, and Categories

Category Description	DISCONNECTS
Туре	Disconnect Switches

Packaging

Carton	1
Weight Per each	2.82

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Heavy Duty Industrial and/or Washdown
standard	cULus Listed