

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **HBLDS60AC NM Sloped Disc, 60A Unfused, 4X, Hblac1** *Hubbell Wiring Devices*

3	
Catalog Number	HBLDS60AC
Manufacturer	Hubbell Wiring Devices
Description	Industrial Grade, Motor Disconnect, Unfused, 3 Pole, 60A 600V Ac, Screw Terminals, IP69K, Nema Type 4X, 12 Non-Metallic Sloped Top Enclosure, AC1 Aux Contact, Culus, NSF, Ce, UI 508 / UI 60947-4-1a
Weight per unit	6.1 (lbs/each)
Product Category	20240715144038
eatures	
operating cycles	10,000
Descriptions	
Description	NM SLOPED DISC, 60A UNFUSED, 4X, HBLAC1
extra long description	HWDK HBLDS60AC NM SLOPED DISC, 60A
Features	NEC section 430.102(B) requires each motor controller to have a disconnect within line of sight from the motor and driven equipment. Hubbell's Circuit-Lock® Unfused Disconnect Switches are UL listed as a manual motor controller and also "suitable as a motor disconnect" and meet these code requirements.
Long Description	Industrial Grade, Motor Disconnect, Unfused, 3 Pole, 60A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure, AC1 Aux Contact, cULus, NSF, CE, UL 508 / UL 60947-4-1A
Product Type	NM Sloped Disc, 60A Unfused, 4X, Hblac1
Manufacturer Information	
Brand	WIRING DEVICE-KELLEMS
GTIN	00783585763231
Manufacturers Part Number	HBLDS60AC
series	Non-Fused
UPC	783585763231
Taxonomies, Classifications, and Ca	ategories
Category Description	Funda O Funda Annonamina
Туре	Disconnect Switches
Packaging	
Carton	1
Weight Per each	6.11

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Heavy Duty Industrial and/or Washdown
Enclosure	IP69k and UL Type 4X, 12
environmental conditions	Indoor and Outdoor
standard	cULus Listed