

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



IPLD6004 4 Port 600MCM Nsi Industries

Catalog Number	IPLD6004	
Manufacturer	Nsi Industries	
Description	The Polaris IPLD600-4 Multi-Tap Dual-Sided Entry Connector Features 4 Ports Sized For 600 MCM - 6 Awg Wires. The Body Is Made From Aluminum Alloy Wrapped In A Layer Of Plastisol Insulation. Each Dual-Sided Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additional Supplies. Designed For Use In A Wide Range Of Splicing Applications, Including Installation In Cable Trays	
Weight per unit		
Product Category	Large Terminals & Connectors	
Features		
Material	Aluminum	
Number of Conductors	4	
Poles	1	
Voltage Rating	600 V	
Warranty	1 YEAR	
Wire Size	600 MCM-6 AWG	
Wire Type	Class B & C	
Material, Color, and Finish		
Color	Black	
Finish	Plastisol Insulated	
Dimensions and Weight		
Size	L=5.850 - W=2.960 - H=3.030	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	•		
INCC	rın	1110	nc
Desc			
-			

Descriptions Description	4 PORT 600MCM	
extra long description	NSI IPLD600-4 POLARIS Ins Multi-Tap	
Features	The Polaris IPLD600-4 4-Port Dual-Sided Connector provides the simplest solution for forming a secure connection between up to four conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 600 MCM - 6 AWG wires and rated for 600V, this pre-insulated connector comes pre-loaded with an oxide inhibitor and installs faster than traditional uninsulated connector options using just a hex key and torque wrench. The aluminum alloy body is wrapped in high-dielectric stre	
Long Description	The Polaris IPLD600-4 Multi-Tap Dual-Sided Entry Connector features 4 ports sized for 600 MCM - 6 AWG wires. The body is made from aluminum alloy wrapped in a layer of plastisol insulation. Each dual-sided port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex screws used to tighten the connections. Installs with a hex key and torque wrench, without any tape or additional supplies. Designed for use in a wide range of splicing applications, including installation in cable trays	
Product Type	Polaris Ins Multi-Tap 600 4 Port Dse	
Special Features	(4) 600 MCM-6 AWG - Dual Rated	
Manufacturer Information		
Brand	Polaris	
GTIN	00662381789518	
Manufacturers Part Number	IPLD600-4	
UPC	662381789518	
Taxonomies, Classifications, and (Categories	
Category Description	Comp & Mech Lugs and Butt Splices	
Туре	Double Sided Entry	
Packaging		
Carton	2	
Weight Per each	1.7	
Uses, Certifications, and Standard	ls	
Application	Wire Termination	
environmental conditions	75 C	
standard	UL 486A/B	

Temperature Rating 75 C