

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Special Features

ISE73 1-2STR Ins SVC Ent SLV

Nsi Industries	SVO LIIL SEV
Catalog Number	ISE73
Manufacturer	Nsi Industries
Description	Pre-Insulated Service Entry Sleeves 1-2 STR: Pre-Insulated Service Entry Sleeves Are Used For Fast and Easy Installation With Standard Tools. For Combinations Of Aluminum-Aluminum and Aluminum-Copper Conductors. Meets The Requirements Of Ansi C119.4. Rated 600 Volts.
Weight per unit	0.0600 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
insulation	Insulated
Material	Aluminum
Number of Wires	2
Voltage Rating	600 V
Warranty	1 YEAR
Wire Size	Main 2 ACSR 1-2 STR - Tap 2 ACSR 1-2 STR
Material, Color, and Finish	
Color	Red (Main) - Red (Tap)
Dimensions and Weight	
Size	L=2 3/4
Descriptions	
Description	1-2STR INS SVC ENT SLV
extra long description	NSI ISE73 Ins Serv Ent Sleeve RED-O
Features	Pre-Insulated Service Entry Sleeves 1-2 Str: Pre-insulated service entry sleeves are used for fast and easy installation with standard tools. For combinations of aluminum-aluminum and aluminum-copper conductors. Meets the requirements of ANSI C119.4. Rated 600 Volts.
Long Description	Pre-Insulated Service Entry Sleeves 1-2 Str: Pre-insulated service entry sleeves are used for fast and easy installation with standard tools. For combinations of aluminum-aluminum and aluminum-copper conductors. Meets the requirements of ANSI C119.4. Rated 600 Volts.
Product Type	Ins Serv Ent Sleeve Red-Orn 1-2 STR

Main-2(ACSR) 1-2(STR) Red - Tap - 2(ACSR) 1-2(STR) Red



Type

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	NSi
GTIN	00662381028112
Manufacturers Part Number	ISE73
UPC	662381028112

Taxonomies, Classifications, and Categories

Packaging		
Carton	1	
- .		

Servie Entrance Sleeves

Package 50
Weight Per each 0.06

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C