

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Size

## IT04C 4-14AWG 2PRT, Os Insltd Tap Conn Nsi Industries

Catalog Number	ITO4C
Manufacturer	Nsi Industries
Description	The Polaris Ito-4C Multi-Tap Offset Dual-Side Entry Vision Tap Connector Features 2 Ports Sized For 4 - 14 Awg Wires. The Clear Body Allows Users to See Their Conductor Placement and Is Wrapped In A Layer Of Plastisol Insulation. Each Port Is Pre-Loaded With An Oxide Inhibitor, With Removable Access Plugs Over The Hex Screws Used to Tighten The Connections. Installs With A Hex Key and Torque Wrench, Without Any Tape or Additional Supplies. Designed For Use In A Wide Range Of Splicing Applications, Includin
Weight per unit	
Product Category	·
Features	
Material	Aluminum
Number of Conductors	2
Poles	1
Voltage Rating	600
Warranty	1 YEAR
Wire Size	4-14 AWG
Wire Type	Class B & C
Material, Color, and Finish	
Color	Clear
Finish	Plastisol Insulated
Dimensions and Weight	
C:	L 1 1 2 0 W 1 2 5 0 LL 1 2 4 0

L=1.120 - W=1.250 - H=1.348



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	4-14AWG 2PRT,OS INSLTD TAP CONN
extra long description	NSI ITO-4C POLARIS Vision Tap 2 Por
Features	The Polaris ITO-4C 2-Port Offset Dual-Sided Connector provides
	the simplest solution for forming a secure connection between
	two conductors in applications including cable trays, panel boards, ducts, raceways or troughs. Sized for 4 - 14 AWG wires
	and rated for 600V, this pre-insulated connector comes
	pre-loaded with an oxide inhibitor and installs faster than
	traditional uninsulated connector options using just a hex key
	and torque wrench. The clear body lets installers see their work
	for optimal conducto
Long Description	The Polaris ITO-4C Multi-Tap Offset Dual-Side Entry Vision Tap
	Connector features 2 ports sized for 4 - 14 AWG wires. The clear
	body allows users to see their conductor placement and is
	wrapped in a layer of plastisol insulation. Each port is pre-loaded with an oxide inhibitor, with removable access plugs over the hex
	screws used to tighten the connections. Installs with a hex key
	and torque wrench, without any tape or additional supplies.
	Designed for use in a wide range of splicing applications, includin
Product Type	Polaris Vision Tap 2 Port 4 Os
Special Features	(2) 4-14 AWG - Dual Rated - Offset Ports
Manufacturer Information	
Brand	NSi
GTIN	00662381996558
Manufacturers Part Number	ITO-4C
UPC	662381996558
Taxonomies, Classifications, and Cate	<del>-</del>
Category Description	TERMINALS
Туре	Offset Entry
Packaging	
Carton	12
Weight Per each	0.06
Uses, Certifications, and Standards	
Application	Wire Termination
Enclosure	Clear Plastisol
environmental conditions	Dry Location Only
standard Tomporature Pating	UL 486A/B
Temperature Rating	90