

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## ITCSN15009 Heat Shrink Heavywall Cable Sleeve ITCSN1500, 9" Minnesota Mining (3M)

| Catalog Number                   | ITCSN15009  |
|----------------------------------|---|
| Manufacturer                     | Minnesota Mining (3M)   |
| Description                      | 3M™ Heat Shrink Cable Sleeve Itcsn Is A Heavy Wall Sleeve That                            |
|                                  | Provides Abrasion, Corrosion and Chemical Resistance. This                                |
|                                  | Sleeve Has A 3:1 Shrink Ratio to Offer Electrical Insulation For 1                        |
|                                  | KV Rated Applications. It Features A Cross Linked Polyolefin                              |
|                                  | Construction That Provides Moisture Seal Protection.                                      |
| Weight per unit                  | 0.1968 (lbs/each)   |
| Product Category                 | Insulating Materials  |
| Descriptions                     |   |
| Description                      | HEAT SHRINK HEAVYWALL CABLE SLEEVE ITCSN1500, 9"  |
| extra long description           | 3M 7000057990 3M™ Heat Shrink Heavy   |
| Features                         | 3M™ Heat Shrink Cable Sleeve ITCSN is a split resistant sleeve                            |
|                                  | with a factory applied adhesive/sealant that offers reliable                              |
|                                  | performance for electrical splices, connections and terminations.                         |
|                                  | It is perfect for insulating secondary splices, direct buried,                            |
|                                  | submersible or dig in repairs, as well as physical protection of                          |
|                                  | high voltage, air insulated connectors or lugs. It withstands                             |
|                                  | temperatures of 67 to 230 degrees F (55 to 110 degrees C). UL                             |
|                                  | Listed, CSA Certified and RoHS 2011/65/EU Compliant.                                      |
| Long Description                 | 3M™ Heat Shrink Cable Sleeve ITCSN is a heavy wall sleeve that                            |
|                                  | provides abrasion, corrosion and chemical resistance. This sleeve                         |
|                                  | has a 3:1 shrink ratio to offer electrical insulation for 1 kV rated                      |
|                                  | applications. It features a cross linked polyolefin construction                          |
| Product Type                     | that provides moisture seal protection.<br>3M™ Heat Shrink Heavy-Wall Cable Sleeves Itcsn |
| • .                              | Sivi Tieat Silillik Heavy-Wall Cable Sleeves Itcsil                                       |
| Manufacturer Information         |   |
| Brand                            | 3M  |
| GTIN                             | 00054007088974  |
| Manufacturers Part Number        | IT1.500BK9"S  |
| UPC                              | 054007088974  |
| Taxonomies, Classifications, and | l Categories  |
| Category Description             | HEAT/COLD SHRINK  |
| Туре                             | Heavy Wall  |
| Packaging                        |   |
| Carton                           | 1   |
| Package                          | 10  |
| Weight Per each                  | 0.1968  |
|                                  |   |

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Uses, Certifications, and Standards |         |  |
|-------------------------------------|---------|--|
| standard                            | UL, CSA |  |