


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





JDL200 200A 600V Class J Time Delay Fuse Edison Fuses

Catalog Number	JDL200
Manufacturer	Edison Fuses
Description	Eaton Edison Series JDL Fuse, Time-Delay Current-Limiting Fuse, Non-Indicating, 200 A, Dual, J, Non-Indicating, 200 Kaic, 5, 600 V
Weight per unit	0.8000 (lbs/each)
Product Category	Dual Flement

Features

amperage rating	200
amps	200
dimensions	5.7500 IN X 1.6300 IN X 1.6300 IN
Fuse Class	Class J
Fuse Type	Class J Time Delay Fuses
interrupt rating	200 kAIC
media	Yes
Voltage	600V
Voltage Rating	600 V

Descriptions

Description	200A 600V CLASS J TIME DELAY FUSE
extra long description	MOR T626-JDL200 Class J Time Delay
Features	Edison's UL Class J fuse products are offered in both Dual-Element Time-Delay (JDL) and Fast-Acting (JFL) types. Both types have 200,000 amp interrupting rating at 600Vac RMS Sym amps. Their small physical size and high performance characteristics makes Class J fuses ideal for any space-limited applications. Edison's JFL fuses are best suited for the protection of non-inductive loads such as resistive heating and lighting circuits.
Long Description	Eaton Edison series JDL fuse, Time-delay current-limiting fuse, Non-indicating, 200 A, Dual, J, Non-indicating, 200 kAIC, 5, 600 V
Product Type	Class J Time Delay Fuses 600V 200a
Special Features	Non-Indicating
nufacturer Information	

Manufacturer Information

Brand	Eaton
GTIN	00782634803546
Manufacturers Part Number	JDL200
UPC	782634803546



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categ	ories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	1
Weight Per each	0.8
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	RoHS Compliant,CE Marked