

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



JDL3 3A 600V Class J Time Delay Fuse Edison Fuses

| Catalog Number | JDL3 |
|------------------|--|
| Manufacturer | Edison Fuses |
| Description | Eaton Edison Series JDL Fuse, Time-Delay Current-Limiting Fuse, Non-Indicating, 3 A, Class J, 200 Kaic, Standard, 10, 600 V |
| Weight per unit | 0.1000 (lbs/each) |
| Product Category | Dual Element |
| Features | |
| amperage rating | 3 A |
| amps | 3 |
| class | Class J |
| dimensions | 2.2500 IN X 0.8100 IN X 0.8100 IN |
| Fuse Type | Class J Time Delay Fuses |
| interrupt rating | 200 kAIC |
| media | Yes |
| Voltage | 600V |
| Voltage Rating | 600 V |
| - | |

Descriptions

GTIN

UPC

Manufacturers Part Number

| Description | 3A 600V CLASS J TIME DELAY FUSE |
|--------------------------|--|
| extra long description | MOR T626-JDL3 Class J Time Delay Fu |
| Features | Edison's UL Class J fuse products are offered in both Dual-Element Time-Delay (JDL) and Fast-Acting (JFL) types. Both types have 200,000 amp interrupting rating at 600Vac RMS Sym amps. Their small physical size and high performance characteristics makes Class J fuses ideal for any space-limited applications. Edison's JFL fuses are best suited for the protection of non-inductive loads such as resistive heating and lighting circuits. |
| Long Description | Eaton Edison series JDL fuse, Time-delay current-limiting fuse, Non-indicating, 3 A, Class J, 200 kAIC, Standard, 10, 600 V |
| Product Type | Class J Time Delay Fuses 600V 3a |
| Special Features | Non-Indicating |
| Manufacturer Information | |
| Brand | Eaton |

00782634803348

782634803348

JDL3



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

| Category Description | Fuses & Fuse Accessories |
|----------------------|--------------------------|
| Туре | FUSE |
| ackaging | |
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.1 |

Uses, Certifications, and Standards

| Application | Datacenters - Facilities: Critical Power |
|-------------|---|
| standard | CSA Certified, UL Listed, RoHS Compliant, CE Marked |