



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



KRPC601SP 601A 600V TD Low Peak Class L Fuse

Bussmann Fuses

Catalog Number	KRPC601SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class L Fuse, KRP-C, Time-Delay, Current Limiting Fuse, 601 A, Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	3.7 (lbs/each)
Product Category	Dual Element

Features

amperage rating	601
connection	Bolted Blade End X Bolted Blade End
dimensions	8.6300 IN X 2.5300 IN X 2.5300 IN
Fuse Class	Class L
interrupt rating	100 kA at 300 kAIC Vdc300 kAIC at 600 Vac
Material	Melamine Glass Tube
media	Yes
Response Time	4 sec at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size	2.50 In Diameter X 8.63 In Length
------	-----------------------------------

Descriptions

Description	601A 600V TD LOW PEAK CLASS L FUSE
extra long description	BUSS KRP-C-601SP LOW-PEAK TIME-DELA
Features	Bussmann's broad line of UL Class L fuses includes the KRP-C-SP Low-Peak family of fuses offering unsurpassed dual-element, current-limiting, time-delay performance and interrupting ratings of 300kA RMS Sym. Complementing the Low-Peak family are our Limitron products offering both Fast-acting and economical time-delay performance in our KTU, KLU, and KRP-CL products
Long Description	Eaton Bussmann Series Class L fuse, KRP-C, time-delay, current limiting fuse, 601 A, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc
Product Type	Low-Peak Time-Delay 300K
Special Features	Silver Plated End Bell

Manufacturer Information

Brand	Eaton
GTIN	00051712605069
Manufacturers Part Number	KRP-C-601SP
UPC	051712605069



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description.....Fuses & Fuse Accessories

Type.....FUSE

Packaging

Carton.....1

Weight Per each.....3.74

Uses, Certifications, and Standards

Application.....Ind Facilities & Factories - Facility: Safety and Security Systems

standard.....RoHS Compliant,CE Marked