

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **LL28SS 3/4" SS6 LL FM8 CNDT BCG** *Crouse-Hinds*

Catalog Number	LL28SS
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Conduit Body, Cover and Gasket, Stainless Steel, LL Shape, 3/4"
Weight per unit	1.9 (lbs/each)
Product Category	Bodies & Covers
Features	
dimensions	5.8000 IN X 2.4600 IN X 1.7100 IN
Dimensions and Weight	
Height	1.63
Hub Size	3/4 in
Length	5.72
Width	1.63
Descriptions	
Description	3/4" SS6 LL FM8 CNDT BCG
extra long description	CRS-H LL28SS 3/4 CNDT BODY CVR & GS
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 8 bodies are offered in seven different shapes to provide the most flexible offering on the market. Form 8 Condulet outlet bodies provide more room for heavier conductors. Many shapes and sizes are available for rigid threaded conduit. Two cover screws on all body sizes provide tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 conduit body, cover and gasket, Stainless steel, LL shape, 3/4"
Product Type	3/4 CNDT Body CVR & GSKT Stainless Steel
Special Features	With Cover and Neoprene Gasket
Manufacturer Information Brand	Eaton

#### Ma

Brand	Eaton
GTIN	00662276160439
Manufacturers Part Number	LL28SS
UPC	662276160439

### **Taxonomies, Classifications, and Categories**

Туре	Conduit body, cover and gasket
------	--------------------------------



standard

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	1.91
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514B, CSA C22.2