

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

Alum

1220 Elm Street 75482-0000, TX Sulphur Springs Phone: 903-885-0024 Fax: 903-885-0352



### **LL59 1-1/2" Alu LL MK9 Conduit Body** *Crouse-Hinds*

Catalog Number	LL59
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Mark 9 Conduit Outlet Body,
	Copper-Free Aluminum, LL Shape, 1-1/2"
Weight per unit	1.3 (lbs/each)

#### **Features**

dimensions 7.8000 IN X 2.8100 IN X 3.5000 IN

#### Material, Color, and Finish

Finish Untreated

#### **Dimensions and Weight**

**Product Category** 

Height	2-3/4 1.1/2 ip
Hub Size	1-1/2 in
Length	7-3/4
Width	3-7/16

#### **Descriptions**

Description	1-1/2" ALU LL MK9 CONDUIT BODY
extra long description	CRS-H LL59 1 1/2 LL MARK 9 CNDT BOD
Features	Mark 9 copper-free aluminum conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide for access to conductors for maintenance and future system changes. Mark 9 bodies are offered in seven different shapes, and they provide more room for heavier conductors.
Long Description	Eaton Crouse-Hinds series Condulet Mark 9 conduit outlet body, Copper-free aluminum, LL shape, 1-1/2"
Product Type	1 1/2 LL Mark 9 CNDT Body
	-

#### **Manufacturer Information**

Brand	Eaton
GTIN	00782274525204
Manufacturers Part Number	LL59
UPC	782274525204

### **Taxonomies, Classifications, and Categories**

Category Description	Form 9 condulets, covers & gaskets
Туре	Conduit outlet body



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1220 Elm Street 75482-0000, TX Sulphur Springs Phone: 903-885-0024 Fax: 903-885-0352

Packaging	
Carton	1
Package	2
Weight Per each	1.33
Uses, Certifications, and Standards	<b>3</b>
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D