

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPCC30 30A 600V TD Class CC Low Peak Fuse Bussmann Fuses

w	
Catalog Number	LPCC30
Manufacturer	Bussmann Fuses
Description	Low Peak Fuse, Time Delay Fuse Speed, Class CC Fuse, 12 S @ 200% Response Time, 30 A, 600 V Ac;300 V DC, Melamine Tube Material, Dual Element, 0.41 In Diameter, 1.5 IN38.1 MM Overa Length, 0.02 LB
Weight per unit	0.0200 (lbs/each)
Product Category	Current Limiting
eatures	
amperage rating	30
connection	Ferrule End X Ferrule End
dimensions	0.4100 IN X 0.4100 IN X 1.5000 IN
element	Dual
media	Yes
imensions and Weight	
Size	13/32 In Diameter X 1-1/2 In Length
escriptions	
Description	30A 600V TD CLASS CC LOW PEAK FUSE
extra long description	BUSS LP-CC-30 LOW PEAK CC TIME DELA
Features	Bussmann's Class CC fuses set the standard in Class CC fuse performance in the industry. Recognized for their superior performance, Bussmann has the right product for your circuit and equipment protection needs. These branch circuit rated, 600v, 200,000a IR fuses offer exceptional protection in the smallest package of any UL class of fuses. Choose from the ultimate protection provided by our Low Peak LP-CC fuses, the time delay of our FNQ-R's for your control transformer and similar control applications or
Special Features	Rejection Style
Nanufacturer Information	
Brand	COOPER BUSSMANN
GTIN	00051712180313
UPC	051712180313
axonomies, Classifications, and	Categories
Category Description	
Туре	51.105



$E_{\text{LLIOTT}} E_{\text{LECTRIC}} S_{\text{UPPLY}}$

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

D	
Park	aging
I aun	aying

laonaging		
Carton	10	
Weight Per each	0.02	
Uses, Certifications, and Standa	ards	
standard	UL Listed ,CSA Certified,RoHS Compliant,CE Marked	