

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPJ250SP Low Peak Class J TD Fuse

Bussmann Fuses

| Catalog Number | LPJ250SP |
|---------------------------|--|
| Manufacturer | Bussmann Fuses |
| Description | Eaton Bussmann Series LPJ Fuse, Bussmann Series Class J Fuse, LPJ, Time-Delay, Dual-Element Current Limiting Fuse, 250 A, Non-Idicating Fuse, Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC |
| Weight per unit | 1.6 (lbs/each) |
| Product Category | Dual Element |
| eatures | |
| dimensions | 2.1100 IN X 2.1100 IN X 7.1200 IN |
| media | Yes |
| escriptions | |
| Description | LOW PEAK CLASS J TD FUSE |
| extra long description | BUSS LPJ-250SP LOW PEAK CLASS J T/D |
| Features | Bussmann's UL Class J fuse products extend both our Low-Peak family of products with our LPJ_SP and LPJ_SPI dual-element, time-delay fuses as well as our Limitron line offering fast-acting JKS fuses. The LPJ fuses provide industry leading 300,000 amp interrupting rating at 600Vac RMS Sym and 100kA Vdc while delivering a minimum of 10 seconds of 500 percent rated currer ride-through performance which is ideal for sizing of high inrush loads. The LPJ products are available with optional permanent replace fu |
| Long Description | Eaton Bussmann series LPJ fuse, Bussmann Series Class J fuse, LPJ, time-delay, dual-element current limiting fuse, 250 A, non-idicating fuse, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc |
| Product Type | Low Peak Class J T/D |
| lanufacturer Information | |
| Brand | Eaton |
| GTIN | 00051712523189 |
| Manufacturers Part Number | LPJ-250SP |
| UPC | 051712523189 |

| Category Description | Fuses & Fuse Accessories |
|----------------------|--------------------------|
| Туре | FUSE |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Pac | kag | ıng |
|-----|-----|-----|
| | 0 | ٠ 4 |

| Carton | 1 |
|-----------------|------|
| Weight Per each | 1.55 |

Uses, Certifications, and Standards

| Application | Ind Facilities & Factories - Facility: Safety and Security Systems |
|-------------|--|
| standard | CSA Certified ,UL Listed,RoHS Compliant |