



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

13405 Stemmons Frwy
75234-0000, TX Farmers Branch
Phone: 972-206-0016
Fax: 972-352-2818



LPSRK60SP Low-Peak Dual Element

Bussmann Fuses

Catalog Number	LPSRK60SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK1 Fuse, LPS-RK, Time-Delay, Dual-Element, Current Limiting Fuse, 60 A, Non-Indicating Fuse, Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	2.6 (lbs/each)
Product Category	Dual Element

Features

amperage rating	60
connection	Ferrule End X Ferrule End
dimensions	5.5000 IN X 1.0600 IN X 1.0600 IN
element	Dual
Fuse Class	Class RK1
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size	1.06 In Diameter X 5.50 In Length
------	-----------------------------------

Descriptions

Description	LOW-PEAK DUAL ELEMENT
extra long description	BUSS LPS-RK-60SP LOW-PEAK DUAL ELEM
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann Series Class RK1 fuse, LPS-RK, time-delay, dual-element, current limiting fuse, 60 A, non-indicating fuse, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc
Product Type	Low-Peak Dual Element
Special Features	Electrically Isolated End Cap

Manufacturer Information

Brand	Bussmann Fuses
Manufacturers Part Number	LPS-RK-60SP



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

13405 Stemmons Frwy
75234-0000, TX Farmers Branch
Phone: 972-206-0016
Fax: 972-352-2818

Taxonomies, Classifications, and Categories

Type FUZE

Packaging

Carton 1

Weight Per each 2.6

Uses, Certifications, and Standards

Application Ind Facilities & Factories - Facility: Safety and Security Systems

standard CE Marked