

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

LPSRK60SPI 60A Indicating Low Peak Dual Bussmann Fuses

Catalog Number	LPSRK60SPI
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK1 Fuse, LPS-RK, Time-Delay,
	Dual-Element, Current Limiting Fuse, 60 A, Indicating Fuse,
	Interrupting Rating Of 300 Ka At 600 Vac
Weight per unit	
Product Category	Small Dimension Fuses
eatures	
amperage rating	60
connection	Ferrule End X Ferrule End
dimensions	5.5000 IN X 1.0600 IN X 1.0600 IN
element	Dual
Fuse Class	Class RK1
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
media	Ma a
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
imensions and Weight	
Size	1.06 In Diameter X 5.50 In Length
escriptions Description	60A INDICATING LOW PEAK DUAL
Description extra long description	
<b>š</b>	
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting,
	time-delay fuses (LPN-RK and LPS-RK) which are also available
	with optional indication on select ratings (see product data
	sheet). Complementing the Low-Peak product offering is
	Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R
	KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann Series Class RK1 fuse, LPS-RK, time-delay,
	dual-element, current limiting fuse, 60 A, indicating fuse,
	interrupting rating of 300 kA at 600 Vac
Product Type	Indicating LPS-RK-60SP
Special Features	Electrically Isolated End Cap



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	Eaton Bussmann series
GTIN	00051712626309
Manufacturers Part Number	LPS-RK-60SPI
UPC	051712626309
Taxonomies, Classifications, and Ca	tegories
Category Description	Fuses & Fuse Accessories
Туре	FUSE
Packaging	
Carton	10
Weight Per each	0.31
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked