

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LPSRK80SP 80A 600V TD Dual Elem Class RK1 Low Peak Fuse Bussmann Fuses

Catalog Number	LPSRK80SP
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class RK1 Fuse, LPS-RK, Time-Delay,
	Dual-Element, Current Limiting Fuse, 80 A, Non-Indicating Fuse,
	Interrupting Rating Of 300 Ka At 600 Vac and 100 Ka At 300 VDC
Weight per unit	0.4100 (lbs/each)
Product Category	Dual Element

Features

itui c s	
amperage rating	80
class	Class RK1
connection	Blade End X Blade End
dimensions	7.8800 IN X 1.1100 IN X 1.1100 IN
element	Dual
Fuse Class	Class RK1
interrupt rating	300 kAIC at 600 Vac100 kAIC at 300 Vdc
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

Dimensions and Weight

Size	1.	.11	In	Diamet	ter	Χ	7.8	ıl 8	า Lei	ngth	ገ	

Descriptions

Description	80A 600V TD DUAL ELEM CLASS RK1 LOW PEAK FUSE
extra long description	BUSS LPS-RK-80SP LOW-PEAK DUAL ELEM
Features	Bussmann's UL Class RK1 fuse offering includes the industry's most recognized Low-Peak dual-element, current-limiting, time-delay fuses (LPN-RK and LPS-RK) which are also available with optional indication on select ratings (see product data sheet). Complementing the Low-Peak product offering is Bussmann's Limitron family of fast-acting fuses (KTN-R, KTS-R, KWN-R and KWS-R) fuses.
Long Description	Eaton Bussmann Series Class RK1 fuse, LPS-RK, time-delay, dual-element, current limiting fuse, 80 A, non-indicating fuse, interrupting rating of 300 kA at 600 Vac and 100 kA at 300 Vdc
Product Type	Low-Peak Dual Element
Special Features	Electrically Isolated End Cap



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Eaton
GTIN	00051712548434
Manufacturers Part Number	LPS-RK-80SP
UPC	051712548434

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

onaging	
Carton	5
Weight Per each	0.41

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked,RoHS Compliant