

ELLIOTT ELECTRIC SUPPLY No Deliver Lower Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



LT25045G 2-1/2" 45D AI LT Conn, #1/0-8AWG GRND Lug Crouse-Hinds

Catalog Number	LT25045G
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Liquidator Liquidtight Connector, FMC 45° Angle, Aluminum Ground Lug, Non-Insulated, #1/0-8 Awg Lug Size, Malleable Iron, 2-1/2"
Weight per unit	5.8 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
connection	Threaded
dimensions	8.3100 IN X 4.0000 IN X 8.3100 IN
installation type	THREADED
Material, Color, and Finish	
Color	MALLEABLE IRON
Descriptions	
Description	2-1/2" 45D AL LT CONN, #1/0-8AWG GRND LUG
extra long description	MIDWEST LT25045G 2 1/2 LT 45 DEGREE
Features	Liquidtight fittings from Eaton's Crouse-Hinds Division are designed to protect conductors from mechanical damage due to vibration and movement while sealing out cutting oils, coolants, water, and dust. Typical applications include the wiring of machine tools, motors, transformers, food processing equipment, robotics, air conditioning units and illuminated signs To meet any customer preference, Crouse-Hinds series liquidtight fittings are available in a variety sizes, configurations and materials, inclu
Long Description	Eaton Crouse-Hinds series Liquidator liquidtight connector, FMC, 45° angle, Aluminum ground lug, Non-insulated, #1/0-8 AWG lug size, Malleable iron, 2-1/2"
Product Type	2 1/2 LT 45 Degree Conn Ground Lug
Special Features	With 8 To 1/0 AWG Aluminum Grounding Lug
Vlanufacturer Information Brand	Eaton
GTIN	00784564260277
Manufacturers Part Number	
UPC	784564260277

Taxonomies, Classifications, and Categories

Category Description	METALLIC FITTINGS
Туре	Liquidtight connector



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Trade Size	2 1/2 in
Packaging Carton	1
Weight Per each	5.82
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
standard	UL 467, UL 514B, CSA C22.36