



MILBANK
ENERGY AT WORK

M400-UG-APS-LC



| | | | |
|-------------------------------|--|---------------------------|--|
| Catalog Number | M400-UG-APS-LC | Mounting | Surface Mount |
| Marketing Product Description | 4 Terminal Ring Type Plain Top 1-200 Ampere Main Breaker 24 Branch Circuit | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| UPC | 784572116238 | Jaw Quantity | 4 Terminal |
| Length (IN) | 6 | Bypass Type | No Bypass |
| Width (IN) | 28 | Number of Meter Positions | 1 Position |
| Height (IN) | 40 | Equipment Ground | Ground Bar |
| Brand Name | Milbank | Hub Opening | Plain Top |
| Type | Ring Type Meter Socket | Line Side Wire Range | 6 AWG - 350 kcmil |
| Application | Meter Socket With Main And Load Center | Number Branch Circuits | 12 |
| Standard | UL Listed;Type 3R | Number Of Receptacles | 0 |
| Voltage Rating | Up to 240 Volts Alternating Current | | |
| Amperage Rating | 320 Continuous Ampere | | |
| Phase | 1 Phase | | |
| Frequency Rating | 60 Hertz | | |
| Size | 6L x 28W x 40H | | |
| Number Of Cutouts | 2 | | |
| Cutout Size | Two 200 Ampere Main Breakers | | |
| Cable Entry | Underground | | |
| Terminal | Single Mechanical | | |
| Insulation | Glass Polyester | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.



MILBANK
ENERGY AT WORK

M400-UG-APS-LC



| | | | |
|-------------------------------|--|---------------------------|--|
| Catalog Number | M400-UG-APS-LC | Mounting | Surface Mount |
| Marketing Product Description | 4 Terminal Ring Type Plain Top 1-200 Ampere Main Breaker 24 Branch Circuit | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| UPC | 784572116238 | Jaw Quantity | 4 Terminal |
| Length (IN) | 6 | Bypass Type | No Bypass |
| Width (IN) | 28 | Number of Meter Positions | 1 Position |
| Height (IN) | 40 | Equipment Ground | Ground Bar |
| Brand Name | Milbank | Hub Opening | Plain Top |
| Type | Ring Type Meter Socket | Line Side Wire Range | 6 AWG - 350 kcmil |
| Application | Meter Socket With Main And Load Center | Number Branch Circuits | 12 |
| Standard | UL Listed;Type 3R | Number Of Receptacles | 0 |
| Voltage Rating | Up to 240 Volts Alternating Current | | |
| Amperage Rating | 320 Continuous Ampere | | |
| Phase | 1 Phase | | |
| Frequency Rating | 60 Hertz | | |
| Size | 6L x 28W x 40H | | |
| Number Of Cutouts | 2 | | |
| Cutout Size | Two 200 Ampere Main Breakers | | |
| Cable Entry | Underground | | |
| Terminal | Single Mechanical | | |
| Insulation | Glass Polyester | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.