

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



MDL12R 1/2A 250V 3AG - 1/4'X1-

Bussmann Fuses	
Catalog Number	MDL12R
Manufacturer	Bussmann Fuses
Description	Eaton MDL Series Time-Delay Fuse 0.50A, 250 Vac, 32 VDC (Self Certified)
Weight per unit	0.0100 (lbs/each)
Product Category	Small Dimension Fuses
Features	
amperage rating	0.50A
connection	Ferrule End X Ferrule End
dimensions	X X 1.2598 IN
interrupt rating	35 AIC at 250 Vac10 kAIC at 125 Vac
Material	Glass tubeNickel-plated brass end cap construction
Response Time	60 min at 135%, 120 sec at 200%, 5 sec at 200%
Voltage Rating	250 Vac, 32 Vdc (self certified)
Dimensions and Weight	
Size	1/4 In Diameter X 1-1/4 In Length
Descriptions	
Description	1/2A 250V 3AG - 1/4'X1-
extra long description	EFSE MDL-1/2-R BUSS SMALL DIMENSION
Features	Eaton's Bussmann Division develops and manufactures critical circuit protection, power management and electrical safety products designed to provide innovative circuit and power electronics protection, serving the commercial, data center, electrical vehicle, food and beverage, and other markets.
Long Description	Eaton MDL Series Time-delay fuse 0.50A, 250 Vac, 32 Vdc (self

	certified)
Product Type	Buss Small Dimension Fuse
Special Features	Interrupt Rating 35 Amp at 250 Vac, 10000 Amp at 125 Vac,
-	Material Glass Tube, Nickel Plated Brass Endcap, ROHS Compliant

Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712652094
Manufacturers Part Number	MDL-1/2-R
UPC	051712652094

Taxonomies, Classifications, and Categories

Category Description	GLASS FUSES (and ceramic)
Туре	Time-delay fuse



ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	5
Weight Per each	0.01
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	RoHS Compliant,CE Marked