

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



N500 500 Cu Split Bolt

Nsi Industries			
Catalog Number	N500		
Manufacturer	Nsi Industries		
Description	Copper Split Bolt Connector 500 MCM Copper Split Bolt		
	Connectors Are High-Strength Solderless Service Connectors		
	Made Of High-Copper Alloy For Copper and Copperweld Wires.		
	Type For Two Maximum Wire Sizes.		
Weight per unit			
Product Category	Large Terminals & Connectors		
Features			
Material	Copper		
Number of Conductors	2		
Poles	1		
Voltage Rating	600 V		
Warranty	1 YEAR		
Wire Size	250 - 500 MCM		
Wire Type	Class A & B		
Material, Color, and Finish			
Color	Copper		
Finish	COPPER		
Dimensions and Weight			
Size	L=2.814 - W=1.338		
Descriptions			
Description	500 CU SPLIT BOLT		
extra long description	NSI N-500 Split Bolt Copper 500		
Features	Copper Split Bolt Connector 500 MCM Copper Split Bolt		
	Connectors are high-strength solderless service connectors made		
	of high-copper alloy for copper and copperweld wires. Type for		
	two maximum wire sizes.		
Long Description	Copper Split Bolt Connector 500 MCM Copper Split Bolt		
	Connectors are high-strength solderless service connectors made		
	of high-copper alloy for copper and copperweld wires. Type for		
	two maximum wire sizes.		
Product Type	Split Bolt Copper 500		
Special Features	250-500 MCM - 3 Pack		



ELLIOTT ELECTRIC SUPPLY We Deliver Lower Cost. Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

ve DeliverLower Cost, C	Quality Products,	& Personal Service	Fax: 936-560

Manufacturer Information		
Brand	NSi	
GTIN	00662381020116	
Manufacturers Part Number	N-500	
UPC	662381020116	
Taxonomies, Classifications, and C	Categories	
Category Description	SPLIT BOLTS	
	Copper Split Bolts	
Packaging		
Carton	1	
Package	3	
Weight Per each	0.9	
Uses, Certifications, and Standard	ds	
Application	Wire Termination	
environmental conditions	90 C	
standard	UL486B	
Temperature Rating	90 C	