


## **Straight Non-Metallic Connectors**





For use with non-metallic liquid-tight conduit, type B only. Produced from UV rated plastic for long outdoor life.

| CATALOG<br>NUMBER | UPC/DCI/NAED<br>MFG #018997 | TRADE<br>SIZE | KO<br>SIZE | UNIT<br>PKG | STD<br>PKG | DIM<br>A | DIM<br>B | DIM<br>C |
|-------------------|-----------------------------|---------------|------------|-------------|------------|----------|----------|----------|
| NMLT38            | 54380                       | 3/8           | 1/2        | 25          | 100        | 1.425    | .535     | 1.421    |
| NMLT50            | 54500                       | 1/2           | 1/2        | 25          | 100        | 1.425    | .535     | 1.421    |
| NMLT75            | 54750                       | 3/4           | 3/4        | 10          | 50         | 1.475    | .550     | 1.583    |
| NMLT100           | 54100                       | 1             | 1          | 5           | 25         | 1.950    | .670     | 1.925    |
| NMLT125           | 04223                       | 1-1/4         | 1-1/4      | 5           | 25         | 2.217    | .645     | 2.418    |
| NMLT150           | 04222                       | 1-1/2         | 1-1/2      | 2           | 10         | 2.155    | .660     | 2.700    |
| NMLT200           | 04221                       | 2             | 2          | 2           | 10         | 2.400    | .670     | 3.360    |

Add suffix "BL" to Catalog # when ordering in black, for example NMSC50BL.




## **INSTALLATION INSTRUCTIONS**

Arlington's reusable Liquid-Tight Fittings may be secured to conduit while fully assembled because of our no-spin ferrule. Simply loosen nut, and screw onto conduit. A positive liquid-tight seal is provided by our pressure sensitive internal gland when the nut is tightened. A liquid-tight seal is also assured between the fitting and box by a sealing ring.



## **Straight Non-Metallic Connectors**





For use with non-metallic liquid-tight conduit, type B only. Produced from UV rated plastic for long outdoor life.

| CATALOG<br>NUMBER | UPC/DCI/NAED<br>MFG #018997 | TRADE<br>SIZE | KO<br>SIZE | UNIT<br>PKG | STD<br>PKG | DIM<br>A | DIM<br>B | DIM<br>C |
|-------------------|-----------------------------|---------------|------------|-------------|------------|----------|----------|----------|
| NMLT38            | 54380                       | 3/8           | 1/2        | 25          | 100        | 1.425    | .535     | 1.421    |
| NMLT50            | 54500                       | 1/2           | 1/2        | 25          | 100        | 1.425    | .535     | 1.421    |
| NMLT75            | 54750                       | 3/4           | 3/4        | 10          | 50         | 1.475    | .550     | 1.583    |
| NMLT100           | 54100                       | 1             | 1          | 5           | 25         | 1.950    | .670     | 1.925    |
| NMLT125           | 04223                       | 1-1/4         | 1-1/4      | 5           | 25         | 2.217    | .645     | 2.418    |
| NMLT150           | 04222                       | 1-1/2         | 1-1/2      | 2           | 10         | 2.155    | .660     | 2.700    |
| NMLT200           | 04221                       | 2             | 2          | 2           | 10         | 2.400    | .670     | 3.360    |

Add suffix "BL" to Catalog # when ordering in black, for example NMSC50BL.



## **INSTALLATION INSTRUCTIONS**

Arlington's reusable Liquid-Tight Fittings may be secured to conduit while fully assembled because of our no-spin ferrule. Simply loosen nut, and screw onto conduit. A positive liquid-tight seal is provided by our pressure sensitive internal gland when the nut is tightened. A liquid-tight seal is also assured between the fitting and box by a sealing ring.