

Grounding Bushings and Split Couplings

Grounding Bushings

Description:

Plasti-Bond REDH₂OT grounding bushings are used on threaded PVC-coated rigid conduit to provide a means of grounding conduit through an insulated bushing.

Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 10 trade sizes from 1/2" through 4"
- Aluminum lug for copper or aluminum grounding conductor



GROUNDING BUSHINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2" | PBGLL1 | 0.1 |
| 3/4" | PBGLL2 | 0.1 |
| 1" | PBGLL3 | 0.1 |
| 1-1/4" | PBGLL4 | 0.2 |
| 1-1/2" | PBGLL5 | 0.2 |
| 2" | PBGLL6 | 0.3 |
| 2-1/2" | PBGLL7 | 0.5 |
| 3" | PBGLL8 | 0.7 |
| 3-1/2" | PBGLL9 | 1.0 |
| 4" | PBGLL10 | 1.1 |

Split Couplings

Description:

Plasti-Bond REDH₂OT split couplings are used to connect two pieces of conduit where the conduit can't be turned because of limited clearance between runs or a wall or other obstruction.

Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings



SPLIT COUPLINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2" | PRSSP50 | 0.2 |
| 3/4" | PRSSP75 | 0.3 |
| 1" | PRSSP100 | 0.4 |
| 1-1/4" | PRSSP125 | 0.6 |
| 1-1/2" | PRSSP150 | 0.7 |
| 2" | PRSSP200 | 1.0 |
| 2-1/2" | PRSSP250 | 2.3 |
| 3" | PRSSP300 | 3.0 |
| 3-1/2" | PRSSP350 | 3.8 |
| 4" | PRSSP400 | 4.1 |
| 5" | PRSSP500 | 6.0 |
| 6" | PRSSP600 | 8.6 |

Grounding Bushings and Split Couplings

Grounding Bushings

Description:

Plasti-Bond REDH₂OT grounding bushings are used on threaded PVC-coated rigid conduit to provide a means of grounding conduit through an insulated bushing.

Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 10 trade sizes from 1/2" through 4"
- Aluminum lug for copper or aluminum grounding conductor



GROUNDING BUSHINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2" | PBGLL1 | 0.1 |
| 3/4" | PBGLL2 | 0.1 |
| 1" | PBGLL3 | 0.1 |
| 1-1/4" | PBGLL4 | 0.2 |
| 1-1/2" | PBGLL5 | 0.2 |
| 2" | PBGLL6 | 0.3 |
| 2-1/2" | PBGLL7 | 0.5 |
| 3" | PBGLL8 | 0.7 |
| 3-1/2" | PBGLL9 | 1.0 |
| 4" | PBGLL10 | 1.1 |

Split Couplings

Description:

Plasti-Bond REDH₂OT split couplings are used to connect two pieces of conduit where the conduit can't be turned because of limited clearance between runs or a wall or other obstruction.

Features:

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings



SPLIT COUPLINGS

| PIPE SIZE | FERROUS CATALOG # | NOMINAL WEIGHT |
|-----------|-------------------|----------------|
| 1/2" | PRSSP50 | 0.2 |
| 3/4" | PRSSP75 | 0.3 |
| 1" | PRSSP100 | 0.4 |
| 1-1/4" | PRSSP125 | 0.6 |
| 1-1/2" | PRSSP150 | 0.7 |
| 2" | PRSSP200 | 1.0 |
| 2-1/2" | PRSSP250 | 2.3 |
| 3" | PRSSP300 | 3.0 |
| 3-1/2" | PRSSP350 | 3.8 |
| 4" | PRSSP400 | 4.1 |
| 5" | PRSSP500 | 6.0 |
| 6" | PRSSP600 | 8.6 |