

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Uses, Certifications, and Standards

Application

PFME30LCYUNV3466 Indust-Pfme Led Flood 30000 Lumen 200-480 Vac Crouse-Hinds

Catalog Number	DENTE 201 CVI INIV 2444
Catalog Number Manufacturer	PFME30LCYUNV3466
Description	Crouse-Hinds Eaton Crouse-Hinds Series Pfme Led Floodlight, Cool White, Dimmable Driver, 750W-1000W Hid Equivalent, 50/60 HZ, Polycarbonate Lens, 30000 Lumens, 127 LM/W, Aluminum, Yoke
Woight por unit	Mount, Standard 120° Angle, > 0.90 PF, 277-480 Vac, 242W
Weight per unit Product Category	77.0 (lbs/each) Lighting
	Ligituig
eatures dimensions	20.1600 IN X 4.1700 IN X 12.5000 IN
	20.1000 IN X 4.1700 IN X 12.3000 IN
escriptions Description	INDUST-PFME LED FLOOD 30000 LUMEN 200-480 VAC
extra long description	CRS-H PFME30LCY-UNV34-66 PFME30LCY-
Features	PFME LED floodlights are certified for use wet locations and are
	UL Listed and CSA certified. These floodlights are suitable for
	locations requiring continuous and consistent light levels in
	extreme ambient temperatures and where wet, dusty, hot
	and/or cold conditions exist.
Long Description	Eaton Crouse-Hinds series PFME LED floodlight, Cool white, Dimmable driver, 750W-1000W HID equivalent, 50/60 Hz, Polycarbonate lens, 30000 lumens, 127 lm/W, Aluminum, Yoke mount, Standard 120° angle, > 0.90 PF, 277-480 Vac, 242W
Product Type	PFME30LCY-UNV34-66
lanufacturer Information	
Brand	Eaton
GTIN	00662276966833
Manufacturers Part Number	PFME30LCY-UNV34-66
UPC	662276966833
axonomies, Classifications, and C	Categories
Category Description	LED FLOODLIGHTS, WALLPACKS, BOLLARDS & LANDSCAPE LIGHTING
Туре	FLOODLIGHT
ackaging	
Carton	1
Weight Per each	77

Ind Facilities & Factories - Facility: Lighting and Lighting Controls