

# **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### PLG300 3" Recessed Plug Appleton/Oz Gedney

Catalog Number	PLG300
Manufacturer	Appleton/Oz Gedney
Description	Unilets Recessed Head Close-Up Plug, Size: 3 In, Material:
	Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered
	MNPT, Standard: UI 886 (1203), UI File Number E10444, Csa
	C22.2 No. 25 and 30, Csa 065181, UI Listed For Class I, GR
Weight per unit	2.2 (lbs/each)
Product Category	Bar Hangers & Outlet Box Accy.
eatures	
connection	Tapered MNPT
Material	Malleable Iron
Naterial, Color, and Finish	
Finish	Zinc Electroplate
imensions and Weight	
Size	3
escriptions	
Description	3" RECESSED PLUG
extra long description	APP PLG-300 PLUG 3 REC HEAD CLOSE-
Long Description	UNILETS Recessed Head Close-Up Plug, Size: 3 IN, Material:
	Malleable Iron, Finish: Zinc Electroplate, Connection: Tapered
	MNPT, Standard: UL 886 (1203), UL File Number E10444, CSA
	C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Gr
Product Type	Plug 3 Rec Head Close-Up Iron
Special Features	Accurately tapped, tapered threads for tight, rigid joints and
	ground continuity;Explosionproof, dust-ignitionproof;Smooth,
	rounded integral bushing in each hub protects conductor
	insulation
Ianufacturer Information	
Brand	Appleton
GTIN	00781381652551
Manufacturers Part Number	PLG-300
UPC	781381652551
axonomies, Classifications, and	•
Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs,
	Knockout Plugs
Туре	Recessed Head Close-Up Plug



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### Packaging

Carton	5	
Package	25	
Weight Per each	2.16	

#### Uses, Certifications, and Standards

Application	For Use With Threaded Rigid Metal Conduit and IMC
standard	And Class III; Class II, Groups E, F, G; UL 886 (1203), UL File
	Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed
	For Class I, Groups B, C, D