

# **ELLIOTT ELECTRIC SUPPLY** We Deliver Lower Cost. Quality Products, & Personal Service 3448 Sherwood Way 76901-0000, TX San Angelo Phone: 325-944-7321 Fax: 325-944-1579



Туре

## PLG50RA 1/2" Alu Insert Plug Appleton/Oz Gedney

Catalog Number	PLG50RA
Manufacturer	Appleton/Oz Gedney
Description	Unilets Recessed Head Close-Up Plug, Size: 1/2 In, Material: Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered MNPT, Standard: UI 886 (1203), UI File Number E10444, Csa C22.2 No. 25 and 30, Csa 065181, UI Listed For Class I, Groups
Weight per unit	0.0200 (lbs/each)
Product Category	Bar Hangers & Outlet Box Accy.
Features	
connection	Tapered MNPT
Material	Aluminum
Material, Color, and Finish	
Finish	Epoxy Powder Coat
Dimensions and Weight	
Size	1/2
Descriptions	
Description	1/2" ALU INSERT PLUG
extra long description	APP PLG50RA PLUG 1/2 REC HEAD CLOSE
Long Description	UNILETS Recessed Head Close-Up Plug, Size: 1/2 IN, Material: Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered MNPT, Standard: UL 886 (1203), UL File Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed For Class I, Groups
Product Type	Plug 1/2 Rec Head Close-Up-Alu
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity;Explosionproof, dust-ignitionproof;Smooth, rounded integral bushing in each hub protects conductor insulation
Manufacturer Information	
Brand	Appleton
GTIN	00781381455565
Manufacturers Part Number	PLG50RA
UPC	781381455565
Taxonomies, Classifications, and (	Categories
Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs Knockout Plugs
Turna	

Recessed Head Close-Up Plug



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

3448 Sherwood Way 76901-0000, TX San Angelo Phone: 325-944-7321 Fax: 325-944-1579

### Packaging

Carton	50	
Package	500	
Weight Per each		

#### Uses, Certifications, and Standards

Application	For Use With Threaded Rigid Metal Conduit and IMC
standard	And Class III; Class II, Groups E, F, G; UL 886 (1203), UL File
	Number E10444, CSA C22.2 No. 25 And 30, CSA 065181, UL Listed
	For Class I, Groups A, B, C, D