



PSG480E PWR Supply-1PH 85-264VAC 24VDC@20a

Eaton Corp

Catalog Number	PSG480E
Manufacturer	Eaton Corp
Description	Eaton Power Supply, 480W, Single-Phase, 100-240V Input Voltage, 24 VDC ± 2% Output Voltage, 5.7A Input Current, 20A Output Current, 47-63 HZ, 85-264V, 120-375 VDC, Aluminum Enclosure, Heavy-Duty Screw Terminals
Weight per unit	4.8 (lbs/each)
Product Category	Ac Power Supplies

Features

dimensions	4.7600 IN X 6.3000 IN X 4.5300 IN
Material	Aluminum
media	Yes
Phase	Single-phase
Voltage Rating	85-264 Vac, 100-375 Vdc
Wattage	480W

Descriptions

Description	PWR SUPPLY-1PH 85-264VAC 24VDC@20A
extra long description	ETN PSG480E Power Supply -1PH 85-264VAC 24VDC@20A
Features	The PSG line of general purpose power supplies is used in a wide variety of industrial control applications. Applications include communication networks, sensors, PLCs and many other electrical systems. Each model is equipped with the options of a rugged metal or plastic housing, heavy-duty screw or finger-safe terminals and a variety of protection features. The PSG line offers the flexibility of operating with a universal input voltage of 100-240 Vac. It also provides system protection and continuous oper
Long Description	Eaton Power Supply, 480W, Single-phase, 100-240V input voltage, 24 Vdc ± 2% output voltage, 5.7A input current, 20A output current, 47-63 Hz, 85-264V, 120-375 Vdc, Aluminum enclosure, Heavy-duty screw terminals
Product Type	Power Supply -1PH 85-264VAC, 24VDC@20a
Special Features	Varistor transient surge voltage, surge voltage protection against internal surge, safety class 1 with ground connection, finger-safe cover



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1315 2nd Street MAIP
74361-0000, OK Pryor
Phone: 918-803-0063
Fax: 918-803-0064

Manufacturer Information

Brand	Eaton
GTIN	00786685215488
Manufacturers Part Number	PSG480E
UPC	786685215488

Taxonomies, Classifications, and Categories

Type	General purpose power supply
------	------------------------------

Packaging

Carton	1
Weight Per each	4.8

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Frequency Rating	47-63 Hz
standard	CSA Certified,cULus/UL 60950-1,EN Listed,cUL Certified,UL 508,IEC Rated,RoHS Compliant,German Safety,CE Marked