

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## PT5362LA Duplex Recp Spec GRD 20A/125V La

-F
PT5362LA
Pass & Seymour/Legrand
Plugtail Registered Spec Grade Receptacles, 20A, 125V Plugtail Registered Devices and Connectors Mean That Device Installation Is The Same Regardless Of Skill Level Of The Installer. The UI-Listed Connectors Are Keyed to Ensure Proper Wiring Installation Into Each Receptacle.
0.2300 (lbs/each)
Gen Purpose Recept & Surge Pro
20
Withstands 2000V minimum
Indoor
Nylon
Yes
3
Indoor, Commercial
2
125.0 V
125
Electrical power is expressed in Amps and Volts.
3.281
.625



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	DUPLEX RECP SPEC GRD 20A/125V LA
extra long description	P&S PT5362LA DUP RECEPT SPEC GRD 20
Long Description	PlugTail Registered Spec Grade Receptacles, 20A, 125V PlugTail Registered devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.
Product Type	Dup Recept Spec GRD 20A/125V La
Special Features	Plated steel wrap strap design for maximum durability and corrosion resistance036 inch thick, brass, triple-wipe power contacts for lasting retention. Three drive screws anchor strap to back body and face. No exposed terminals create a finger safe application before, during, and after installation. Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections. Crimped and welded contacts. Ultrasonically welded polycarbonate connector housing secures termin
Manufacturer Information	
Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007091700
Manufacturers Part Number	PT5362-LA
UPC	785007091700
Taxonomies, Classifications, and Cat	egories
Category Description	Residential Switches
Туре	Outlet
Trade Size	
Amperage	20.0
Packaging	
Carton	1
Package	100
Weight Per each	0.23
Uses, Certifications, and Standards	
Application	Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
nema rating	5-20R
standard	FEDSPEC, CULUS, cULus UL498, FEDSPEC