

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PTS20 Solid Pin Term

Nsi Industries

PTS20
Nsi Industries
Solid Pin Terminal For Copper and Aluminum Conductors 2/0 Awg All-Aluminum Pin Terminals Is Designed For Termination Of Both Aluminum and Copper Conductors. The Solid Pin Is Made Of Aluminum and Is Tin-Plated and Pre-Filled With Oxide Inhibitor. A Cover Is Provided For Quick Installation. Rated 600 Volts.
0.1000 (lbs/each)
Large Terminals & Connectors

Features

connection	# 1 Pin
insulation	Plastisol Cover
Material	Aluminum
Number of Conductors	1
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR

Material, Color, and Finish

Color	White
Finish	Tin Plated

Dimensions and Weight

	Size	L=2.20 - OD=.850 - ID=.429 - Pin Dia=.330
--	------	---

Descriptions

scriptions	
Description	SOLID PIN TERM
extra long description	NSI PTS2/0 Aluminum Pin Terminal Al
Features	Solid Pin Terminal for Copper and Aluminum Conductors 2/0 AWG All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Long Description	Solid Pin Terminal for Copper and Aluminum Conductors 2/0 AWG All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Product Type	Aluminum Pin Terminal Al Pin 2/0 Awg
Special Features	2/0 AWG (STR) - # 1 Pin Size



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Inform

Brand	NSi	
GTIN	00662381033451	
Manufacturers Part Number	PTS2/0	
UPC	662381033451	

Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Туре	Solid Pin

Packaging

Carton	1
Weight Per each	0.1

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486
Temperature Rating	90 C