

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

3130 S Dodge Boulevard 85713-0000, AZ Tucson Phone: 520-526-1947 Fax: 520-526-1948

| 20 | | - | - | | Ŀ |
|------|---|---|---|--|---|
| 200 | - | - | - | | Ŀ |
| -201 | | | | | c |
| 200 | | | | | Ē |
| | | | | | ľ |

RE65 2X1-1/2 Reducing Bushing Crouse-Hinds

| Catalog Number | RE65 | |
|----------------------------------|---|--|
| Manufacturer | Crouse-Hinds | |
| Description | Reducing Bushing, 2 to 1-1/2 In Trade Size, Re Model, Electro Galvanized and Aluminum Acrylic Paint, 2.375 In Length, 0.47 LB/Ea | |
| Weight per unit | | |
| Product Category | | |
| Features | | |
| connection | Threaded | |
| dimensions | 2.3800 IN X 1.1200 IN X 2.3800 IN | |
| Material | Feraloy Iron | |
| Material, Color, and Finish | | |
| Finish | Electrogalvanized With Aluminum Acrylic Painted | |
| Dimensions and Weight | | |
| Size | 2 To 1-1/2 In | |
| Descriptions | | |
| Description | 2X1-1/2 REDUCING BUSHING | |
| extra long description | CRS-H RE65 2 TO 1 1/2 REDUCING BUSH | |
| Features | Crouse-Hinds series RE, REA and REC explosionproof reducers are used in rigid/IMC conduit systems to reduce conduit hubs to a smaller size (RE), connect two different sizes of conduit together (REC), or enlarge drilled and tapped openings by one NPT size (REA). PLG explosionproof plugs are used for closing threaded conduit hubs. | |
| Manufacturer Information | | |
| Brand | Eaton | |
| GTIN | 00782274590905 | |
| UPC | 782274590905 | |
| Taxonomies, Classifications, and | Categories | |
| Category Description | Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs | |
| Туре | REDUCER | |
| Packaging Carton | 1 | |
| Package | 10 | |
| Weight Per each | 0.47 | |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

3130 S Dodge Boulevard 85713-0000, AZ Tucson Phone: 520-526-1947 Fax: 520-526-1948

Uses, Certifications, and Standards

| Enclosure | Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II |
|-----------|---|
| | Div 2 Group F G, Class III |
| standard | UL 886, CSA C22.2 |