ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
907 East 2nd Street
88201-0000, NM Roswell
Phone: 575-208-1571
Fax: 575-208-1572



# RSP33 1" Cond 2-Hub Plate

*Crouse-Hinds*

| | |
|---|---|
| Catalog Number | RSP33 |
| Manufacturer | Crouse-Hinds |
| Description | Eaton Crouse-Hinds Series RS/RSM Conduit Hub Plate, 8-1/2" X 4", Feraloy Iron Alloy, 2 Hubs, 1" Trade Size |
| Weight per unit | 2.5 (lbs/each) |
| Product Category | Cast Boxes |

## Features

| | |
|---|---|
| Material | FERALOY IRON ALLOY |

## Dimensions and Weight

| | |
|---|---|
| Height | 8.06 |
| Length | 3.5 |
| Width | 1.13 |

## Descriptions

| | |
|---|---|
| Description | 1" COND 2-HUB PLATE |
| extra long description | CRH RSP33 1 2 HUB PLATE 8 1/2 X 4 S |
| Features | Crouse-Hinds series RS, RSM and RSS junction boxes are installed in conduit systems to act as pull boxes for conductors, provide openings and space for making splices and taps in conductors, provide for branch conduit runs, and provide access to conductors for maintenance and future system changes. RS, RSM and RSS junction boxes are designed with configurable conduit hub plates, permitting a wide range of hub arrangements and sizes. |
| Long Description | Eaton Crouse-Hinds series RS/RSM conduit hub plate, 8-1/2" x 4", Feraloy iron alloy, 2 hubs, 1" trade size |
| Product Type | 1 2 Hub Plate 8 1/2 X 4 Side RS/RSM BX |
| Special Features | Use With 1/2 In Conduit Stem, Connection 3/8 In Male Threaded |

## Manufacturer Information

| | |
|---|---|
| Brand | Eaton |
| GTIN | 00782274598307 |
| Manufacturers Part Number | RSP33 |
| UPC | 782274598307 |

## Taxonomies, Classifications, and Categories

| | |
|---|---|
| Category Description | HUB STYLE BOXES (GUAB, GUAT, ETC) |
| Type | Conduit Hub Plate |

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
907 East 2nd Street
88201-0000, NM Roswell
Phone: 575-208-1571
Fax: 575-208-1572

## Packaging

| | |
|---|---|
| Carton | 1 |
| Package | 2 |
| Weight Per each | 2.45 |

## Uses, Certifications, and Standards

| | |
|---|---|
| Application | Ind Facilities & Factories - Facility: Power Distribution and Control |
| standard | UL 1598 |