



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1715 South Knoxville
72802-0000, AR Russellville
Phone: 479-967-2303
Fax: 479-967-2306



S228V 22-18 Vinyl Spade #8 Stud

Nsi Industries

| | |
|------------------|---|
| Catalog Number | S228V |
| Manufacturer | Nsi Industries |
| Description | 22-18 Awg Vinyl Insulated Spade #8 Stud, 100 Per Pack |
| Weight per unit | 0.1680 (lbs/each) |
| Product Category | Small Terminals & Connectors |

Features

| | |
|---------------------|------------------|
| Material | Vinyl Insulation |
| Number of Terminals | 1 |
| Terminal Size | # 8 |
| Voltage Rating | 300 V |
| Wire Size | 22-18 AWG |

Material, Color, and Finish

| | |
|-------|-----|
| Color | Red |
|-------|-----|

Descriptions

| | |
|------------------------|---|
| Description | 22-18 VINYL SPADE #8 STUD |
| extra long description | NSI S22-8V 22-18 Awg Vinyl Insulate |
| Features | 22-18 AWG Vinyl Insulated Spade #8 Stud, 100 Per Pack |
| Long Description | 22-18 AWG Vinyl Insulated Spade #8 Stud, 100 Per Pack |
| Product Type | 22-18 Awg Vinyl Insulated Spade #8 Stud, 100 Per Pack |
| Special Features | Vinyl Insulated Spade Terminal 22-18 AWG - 100 Pack |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | NSi |
| GTIN | 00662381062680 |
| Manufacturers Part Number | S22-8V |
| UPC | 662381062680 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--------------------------------|
| Category Description | TERMINALS |
| Type | Vinyl Insulated Spade Terminal |

Availability

| | |
|-------------|-----|
| minimum qty | 100 |
|-------------|-----|

Packaging

| | |
|-----------------|-------|
| Carton | 1 |
| Package | 100 |
| Weight Per each | 0.168 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1715 South Knoxville
72802-0000, AR Russellville
Phone: 479-967-2303
Fax: 479-967-2306

Uses, Certifications, and Standards

| | |
|--------------------------|------------------|
| Application | Wire Termination |
| environmental conditions | 75 C |
| standard | cULus |