

## Motion Sensors



Catalog #	Wt.	Description
<b>SO</b>	1500 watt INC capacity, 120V bronze .7 lbs	Motion Sensors for security and welcome lighting.
<b>SO-W</b>	1500 watt INC capacity, 120V white .7 lbs	S Series units have wide 270° field and kits have aluminum lampholders and cover. Center focal range is 50-75 feet.
<b>S2LH</b>	Sensor, twin 150 watt lampholders, coverplate, bronze 1.7 lbs	M Series has 130° detection field, 40 foot center range and non-metallic lampholders and cover. Sensor has 1/2" knuckle mount, adjustable time on and sensitivity controls. Bronze or white finish. UL listed for wet locations.
<b>S2LH-W</b>	Sensor, twin 150 watt lampholders, coverplate, white 1.7 lbs	
<b>MO</b>	Sensor only, 500 watt INC capacity, 120V bronze .5 lbs	
<b>MO-W</b>	Sensor only, 500 watt INC capacity, 120V white .5 lbs	
<b>M2LH</b>	Sensor, twin 150 watt lampholders, coverplate, bronze 1.2 lbs	
<b>M2LH-W</b>	Sensor, twin 150 watt lampholders, coverplate, white 1.2 lbs	
<b>R2LHQ</b>	Sensor, twin 75 watt quartz decorative lampholders and coverplate, bronze, lamps included 1.5 lbs	Quartz motion sensors. Attractive security floodlight set. Powerful 75 watt G8 quartz floods controlled by 130° motion sensor so you save energy – lights only when you need it!
<b>R2LHQ-W</b>	Sensor, twin 75 watt quartz decorative lampholders and coverplate, white, lamps included 1.5 lbs	



# WALKWAY & PATH

## Louverlights



Catalog #	Wt.	Description
<b>587M-VG</b>	Two Tier, 60 watt max. 120V, verdi 2.75 lbs	Louverlights illuminate and accent walkways, driveways and flower beds. Metal construction, verdi finish, frosted glass globes for source brightness reduction, 1/2" hub, UL wet location listed.
<b>583M-VG</b>	Three Tier, 100 watt max. 120V, verdi 3.25 lbs	
<b>GP12BL</b>	Ground post with stabilizers, non-metallic, black 2.50 lbs	Ground post, PVC construction with 4 stabilizers and cap.



# LAMP HOLDERS

## Lampholders



Catalog #	Wt.	Description
<b>101-B</b>	Unshielded, 150 watt max., 120V bronze 0.5 lbs	Cast aluminum units with protective powder paint finish. A variety of unshielded, shielded, and deeply shielded designs for various application requirements. 1/2" cast aluminum swivel knuckle mounting. For use in wet locations. Universal aiming capability. Use PAR lamps outdoors (309 Series can use PAR or BR lamps outdoors).
<b>103-7</b>	Shielded, 150 watt max., 120V bronze 1.25 lbs	
<b>103-74</b>	Shielded, 150 watt max., 120V white 1.25 lbs	
<b>309-M51-ML</b>	Deep shielded, 150 watt max., 120V bronze 3 lbs	
<b>309-M54-ML</b>	Deep shielded, 150 watt max., 120V white 3 lbs	



## Motion Sensors



Catalog #	Wt.	Description
<b>SO</b>	1500 watt INC capacity, 120V bronze .7 lbs	Motion Sensors for security and welcome lighting.
<b>SO-W</b>	1500 watt INC capacity, 120V white .7 lbs	S Series units have wide 270° field and kits have aluminum lampholders and cover. Center focal range is 50-75 feet.
<b>S2LH</b>	Sensor, twin 150 watt lampholders, coverplate, bronze 1.7 lbs	M Series has 130° detection field, 40 foot center range and non-metallic lampholders and cover. Sensor has 1/2" knuckle mount, adjustable time on and sensitivity controls. Bronze or white finish. UL listed for wet locations.
<b>S2LH-W</b>	Sensor, twin 150 watt lampholders, coverplate, white 1.7 lbs	
<b>MO</b>	Sensor only, 500 watt INC capacity, 120V bronze .5 lbs	
<b>MO-W</b>	Sensor only, 500 watt INC capacity, 120V white .5 lbs	
<b>M2LH</b>	Sensor, twin 150 watt lampholders, coverplate, bronze 1.2 lbs	
<b>M2LH-W</b>	Sensor, twin 150 watt lampholders, coverplate, white 1.2 lbs	
<b>R2LHQ</b>	Sensor, twin 75 watt quartz decorative lampholders and coverplate, bronze, lamps included 1.5 lbs	Quartz motion sensors. Attractive security floodlight set. Powerful 75 watt G8 quartz floods controlled by 130° motion sensor so you save energy – lights only when you need it!
<b>R2LHQ-W</b>	Sensor, twin 75 watt quartz decorative lampholders and coverplate, white, lamps included 1.5 lbs	



# WALKWAY & PATH

## Louverlights



Catalog #	Wt.	Description
<b>587M-VG</b>	Two Tier, 60 watt max. 120V, verdi 2.75 lbs	Louverlights illuminate and accent walkways, driveways and flower beds. Metal construction, verdi finish, frosted glass globes for source brightness reduction, 1/2" hub, UL wet location listed.
<b>583M-VG</b>	Three Tier, 100 watt max. 120V, verdi 3.25 lbs	
<b>GP12BL</b>	Ground post with stabilizers, non-metallic, black 2.50 lbs	Ground post, PVC construction with 4 stabilizers and cap.



# LAMP HOLDERS

## Lampholders



Catalog #	Wt.	Description
<b>101-B</b>	Unshielded, 150 watt max., 120V bronze 0.5 lbs	Cast aluminum units with protective powder paint finish. A variety of unshielded, shielded, and deeply shielded designs for various application requirements. 1/2" cast aluminum swivel knuckle mounting. For use in wet locations. Universal aiming capability. Use PAR lamps outdoors (309 Series can use PAR or BR lamps outdoors).
<b>103-7</b>	Shielded, 150 watt max., 120V bronze 1.25 lbs	
<b>103-74</b>	Shielded, 150 watt max., 120V white 1.25 lbs	
<b>309-M51-ML</b>	Deep shielded, 150 watt max., 120V bronze 3 lbs	
<b>309-M54-ML</b>	Deep shielded, 150 watt max., 120V white 3 lbs	

