



Shown actual size: Skylark® preset dimmer and 1-gang Claro® wallplate in almond (AL)

## SKYLARK® dimmers

### product family features

- rocker switch returns light to your favorite light level
- slide up to brighten, down to dim (adjust light to suit any activity)
- coordinating Claro® wallplates available separately (including stainless steel)
- **eco-dim**® model available

### available models

#### source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- electronic low-voltage lighting
- fluorescent lighting
- LED lighting
- dimmable compact fluorescent
- quiet 3-speed fan controls
- quiet 3-speed fan/light controls
- fully variable fan controls

#### control locations

- single pole (one location)
- 3-way (two locations)

**available colors** (see page 12 for color swatches)

#### colors (gloss finish)

- |                        |                 |
|------------------------|-----------------|
| <b>WH</b> white        | <b>GR</b> gray  |
| <b>IV</b> ivory        | <b>BR</b> brown |
| <b>AL</b> almond       | <b>BL</b> black |
| <b>LA</b> light almond |                 |

Questions on installation or selection?  
Call Lutron® 24 hours/7 days a week at  
1.800.523.9466 or visit [www.lutron.com](http://www.lutron.com)

**dimmers with on/off switch**



- rocker switch turns on/off
- slide up to brighten, down to dim
- eco-dim® model guarantees at least 15% energy savings compared to a standard switch

**incandescent/halogen**

|             |       |                |
|-------------|-------|----------------|
| single pole | 600W  | <b>S-600P-</b> |
| single pole | 1000W | <b>S-10P-</b>  |
| 3-way       | 600W  | <b>S-603P-</b> |
| 3-way       | 1000W | <b>S-103P-</b> |

**incandescent/halogen — eco-dim®†**

**NEW**

|                   |      |                 |
|-------------------|------|-----------------|
| single pole/3-way | 600W | <b>S-603PG-</b> |
|-------------------|------|-----------------|

**magnetic low-voltage**

|             |                   |                  |
|-------------|-------------------|------------------|
| single pole | 600 VA<br>(450 W) | <b>SLV-600P-</b> |
| 3-way       | 600 VA<br>(450 W) | <b>SLV-603P-</b> |

Suggested maximum lighting load for magnetic low-voltage dimming is 450W for 600VA products to allow for transformer losses.

**electronic low-voltage\***

|             |      |                   |
|-------------|------|-------------------|
| single pole | 300W | <b>SELV-300P-</b> |
| 3-way       | 300W | <b>SELV-303P-</b> |

\* requires neutral wire connection

† available in white, ivory, almond, and light almond

**dimmers with on/off switch & locator light**



- rocker switch turns on/off
- slide up to brighten, down to dim
- includes locator light

**incandescent/halogen**

|             |       |                  |
|-------------|-------|------------------|
| single pole | 600W  | <b>S-600PNL-</b> |
| single pole | 1000W | <b>S-10PNL-</b>  |
| 3-way       | 600W  | <b>S-603PNL-</b> |
| 3-way       | 1000W | <b>S-103PNL-</b> |

**slide-to-off dimmers**



- slide up to on/brighten, down to dim/off

**incandescent/halogen**

|             |       |                |
|-------------|-------|----------------|
| single pole | 600W  | <b>S-600-</b>  |
| single pole | 1000W | <b>S-1000-</b> |

**See page 77 for available colors.**

To order, add color suffix to model number.

Example: **S-600P- WH**

**fluorescent dimming** with Hi-lume®, Compact SE™, Eco-10®, EcoSystem® ballasts, and Hi-lume® LED



- use with Lutron® 3-wire line-voltage control electronic dimming ballasts
- please refer to the Lutron® Fluorescent Dimming Systems Selection Guide (P/N 366-002) for more information
- no derating if ganged

**fluorescent\***

|             |      |    |                      |
|-------------|------|----|----------------------|
| single pole | 120V | 8A | <b>SF-10P-</b>       |
| single pole | 277V | 6A | <b>SF-12P-277-</b>   |
| 3-way       | 120V | 8A | <b>SF-103P-</b>      |
| 3-way       | 277V | 6A | <b>SF-12P-277-3-</b> |

**LED** (with Hi-lume® LED driver only)\* **NEW**

|             |      |    |                      |
|-------------|------|----|----------------------|
| single pole | 120V | 8A | <b>SF-10P-</b>       |
| single pole | 277V | 6A | <b>SF-12P-277-</b>   |
| 3-way       | 120V | 8A | <b>SF-103P-</b>      |
| 3-way       | 277V | 6A | <b>SF-12P-277-3-</b> |

**LED** (with GRX-TVI 0-10 VDC sink control)\* **NEW**

|             |                                       |                 |
|-------------|---------------------------------------|-----------------|
| single pole | 16A load<br>30 mA control<br>120/277V | <b>SF-10P-</b>  |
| 3-way       | 16A load<br>30 mA control<br>120/277V | <b>SF-103P-</b> |

\* requires neutral wire connection

**fluorescent dimming with Tu-Wire® ballasts**



- use with Lutron® Tu-Wire® line-voltage control electronic dimming ballasts
- for information on using Lutron® dimmers to control Advance® Mark 10® dimming ballasts, visit the Lutron® website at [www.lutron.com/advance](http://www.lutron.com/advance)
- must be derated if ganged

**fluorescent Tu-Wire®**

single pole/3-way 5A **SFTU-5A3P-**

**compact fluorescent dimming with Philips® DIMMABLE Energy Saver CFL** **NEW**



- use **only** with **PHILIPS®** models:  
EL/A  
R30 DIM  
R40 DIM  
PAR38 DIM
- includes locator light
- no derating if ganged
- always turn on, regardless of slider setting
- isolates bulb from unstable line voltage

**screw base dimmable compact fluorescent**

single pole/3-way 200W **SPDC-203P-**

Standard incandescent/halogen dimmers are not UL listed for screw base dimmable compact fluorescent (CFL) lamps.

**See page 77 for available colors.**

To order, add color suffix to model number.

Example: **SF-10P- WH**

**slide-to-off fan control & on/off light switch**



- fan control** (top)
- slide up to on/increase fan speed, down to decrease/off
  - 3 quiet fan speeds for increased comfort
  - for use with only one ceiling paddle fan

- switch** (bottom)
- rocker switch turns light on/off

**quiet 3-speed control & switch**

single pole fan control 1.5A (top) **SFSQ-LF-**  
single pole switch 360W (bottom)  
(incandescent/halogen loads only)

**slide-to-off fan control**



- slide up to on/increase speed, down to decrease/off
- must be derated if ganged

**quiet 3-speed control**

single pole fan control 1.5A **SFSQ-F-**  
2.0A **SFSQ-F-HO-**

for use with only one ceiling paddle fan

**fully variable control**

single pole fan control 5A **SFS-5E-**  
for use with multiple ceiling paddle fans or exhaust fans

**See page 77 for available colors.**  
To order, add color suffix to model number.  
Example: **SFSQ-LF- WH**

**dual slide-to-off dimmers (two loads)**



- dimmers** (left/right)
- slide up to on/brighten, down to dim/off

**incandescent/halogen**

single pole dimmer 300W light (left) **S2-L-**  
single pole dimmer 300W light (right)

**dual slide-to-off fan control & dimmer**



- fan control** (left)
- slide up to on/increase speed, down to decrease/off
  - 3 quiet fan speeds for increased comfort
- dimmer** (right)
- slide up to on/brighten, down to dim/off

**quiet 3-speed control & dimmer**

single pole fan control 1.5A (left) **S2-LFSQ-**  
single pole dimmer 300W (right)  
for use with only one ceiling paddle fan

**fully variable control & dimmer**

single pole fan control 2.5A (left) **S2-LF-**  
single pole dimmer 300W (right)  
for use with multiple ceiling paddle fans or exhaust fans

**replacement knobs**



- standard replacement knobs are available in white, ivory, almond, and light almond

**knobs**

single pole standard knob **SK-**  
split knobs contact customer service



Shown actual size: Skylark® preset dimmer and 1-gang Claro® wallplate in almond (AL)

## SKYLARK® dimmers

### product family features

- rocker switch returns light to your favorite light level
- slide up to brighten, down to dim (adjust light to suit any activity)
- coordinating Claro® wallplates available separately (including stainless steel)
- **eco-dim**® model available

### available models

#### source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- electronic low-voltage lighting
- fluorescent lighting
- LED lighting
- dimmable compact fluorescent
- quiet 3-speed fan controls
- quiet 3-speed fan/light controls
- fully variable fan controls

#### control locations

- single pole (one location)
- 3-way (two locations)

**available colors** (see page 12 for color swatches)

#### colors (gloss finish)

- |                        |                 |
|------------------------|-----------------|
| <b>WH</b> white        | <b>GR</b> gray  |
| <b>IV</b> ivory        | <b>BR</b> brown |
| <b>AL</b> almond       | <b>BL</b> black |
| <b>LA</b> light almond |                 |

Questions on installation or selection?  
Call Lutron® 24 hours/7 days a week at  
1.800.523.9466 or visit [www.lutron.com](http://www.lutron.com)

**dimmers with on/off switch**



- rocker switch turns on/off
- slide up to brighten, down to dim
- eco-dim® model guarantees at least 15% energy savings compared to a standard switch

**incandescent/halogen**

|             |       |                |
|-------------|-------|----------------|
| single pole | 600W  | <b>S-600P-</b> |
| single pole | 1000W | <b>S-10P-</b>  |
| 3-way       | 600W  | <b>S-603P-</b> |
| 3-way       | 1000W | <b>S-103P-</b> |

**incandescent/halogen — eco-dim®†** NEW

|                   |      |                 |
|-------------------|------|-----------------|
| single pole/3-way | 600W | <b>S-603PG-</b> |
|-------------------|------|-----------------|

**magnetic low-voltage**

|             |                   |                  |
|-------------|-------------------|------------------|
| single pole | 600 VA<br>(450 W) | <b>SLV-600P-</b> |
| 3-way       | 600 VA<br>(450 W) | <b>SLV-603P-</b> |

Suggested maximum lighting load for magnetic low-voltage dimming is 450W for 600VA products to allow for transformer losses.

**electronic low-voltage\***

|             |      |                   |
|-------------|------|-------------------|
| single pole | 300W | <b>SELV-300P-</b> |
| 3-way       | 300W | <b>SELV-303P-</b> |

\* requires neutral wire connection

† available in white, ivory, almond, and light almond

**dimmers with on/off switch & locator light**



- rocker switch turns on/off
- slide up to brighten, down to dim
- includes locator light

**incandescent/halogen**

|             |       |                  |
|-------------|-------|------------------|
| single pole | 600W  | <b>S-600PNL-</b> |
| single pole | 1000W | <b>S-10PNL-</b>  |
| 3-way       | 600W  | <b>S-603PNL-</b> |
| 3-way       | 1000W | <b>S-103PNL-</b> |

**slide-to-off dimmers**



- slide up to on/brighten, down to dim/off

**incandescent/halogen**

|             |       |                |
|-------------|-------|----------------|
| single pole | 600W  | <b>S-600-</b>  |
| single pole | 1000W | <b>S-1000-</b> |

**See page 77 for available colors.**

To order, add color suffix to model number.

Example: **S-600P- WH**

**fluorescent dimming** with Hi-lume®, Compact SE™, Eco-10®, EcoSystem® ballasts, and Hi-lume® LED



- use with Lutron® 3-wire line-voltage control electronic dimming ballasts
- please refer to the Lutron® Fluorescent Dimming Systems Selection Guide (P/N 366-002) for more information
- no derating if ganged

**fluorescent\***

|             |      |    |                      |
|-------------|------|----|----------------------|
| single pole | 120V | 8A | <b>SF-10P-</b>       |
| single pole | 277V | 6A | <b>SF-12P-277-</b>   |
| 3-way       | 120V | 8A | <b>SF-103P-</b>      |
| 3-way       | 277V | 6A | <b>SF-12P-277-3-</b> |

**LED** (with Hi-lume® LED driver only)\* **NEW**

|             |      |    |                      |
|-------------|------|----|----------------------|
| single pole | 120V | 8A | <b>SF-10P-</b>       |
| single pole | 277V | 6A | <b>SF-12P-277-</b>   |
| 3-way       | 120V | 8A | <b>SF-103P-</b>      |
| 3-way       | 277V | 6A | <b>SF-12P-277-3-</b> |

**LED** (with GRX-TVI 0-10 VDC sink control)\* **NEW**

|             |                                       |                 |
|-------------|---------------------------------------|-----------------|
| single pole | 16A load<br>30 mA control<br>120/277V | <b>SF-10P-</b>  |
| 3-way       | 16A load<br>30 mA control<br>120/277V | <b>SF-103P-</b> |

\* requires neutral wire connection

**fluorescent dimming with Tu-Wire® ballasts**



- use with Lutron® Tu-Wire® line-voltage control electronic dimming ballasts
- for information on using Lutron® dimmers to control Advance® Mark 10® dimming ballasts, visit the Lutron® website at [www.lutron.com/advance](http://www.lutron.com/advance)
- must be derated if ganged

**fluorescent Tu-Wire®**

single pole/3-way 5A **SFTU-5A3P-**

**compact fluorescent dimming with Philips® DIMMABLE Energy Saver CFL** **NEW**



- use **only** with **PHILIPS®** models:  
EL/A  
R30 DIM  
R40 DIM  
PAR38 DIM
- includes locator light
- no derating if ganged
- always turn on, regardless of slider setting
- isolates bulb from unstable line voltage

**screw base dimmable compact fluorescent**

single pole/3-way 200W **SPDC-203P-**

Standard incandescent/halogen dimmers are not UL listed for screw base dimmable compact fluorescent (CFL) lamps.

**See page 77 for available colors.**

To order, add color suffix to model number.

Example: **SF-10P- WH**

**slide-to-off fan control & on/off light switch**



- fan control** (top)
- slide up to on/increase fan speed, down to decrease/off
  - 3 quiet fan speeds for increased comfort
  - for use with only one ceiling paddle fan

- switch** (bottom)
- rocker switch turns light on/off

**quiet 3-speed control & switch**

single pole fan control 1.5A (top) **SFSQ-LF-**  
 single pole switch 360W (bottom)  
 (incandescent/halogen loads only)

**slide-to-off fan control**



- slide up to on/increase speed, down to decrease/off
- must be derated if ganged

**quiet 3-speed control**

single pole fan control 1.5A **SFSQ-F-**  
 2.0A **SFSQ-F-HO-**  
 for use with only one ceiling paddle fan

**fully variable control**

single pole fan control 5A **SFS-5E-**  
 for use with multiple ceiling paddle fans or exhaust fans

**See page 77 for available colors.**  
 To order, add color suffix to model number.  
 Example: **SFSQ-LF- WH**

**dual slide-to-off dimmers (two loads)**



- dimmers** (left/right)
- slide up to on/brighten, down to dim/off

**incandescent/halogen**

single pole dimmer 300W light (left) **S2-L-**  
 single pole dimmer 300W light (right)

**dual slide-to-off fan control & dimmer**



- fan control** (left)
- slide up to on/increase speed, down to decrease/off
  - 3 quiet fan speeds for increased comfort
- dimmer** (right)
- slide up to on/brighten, down to dim/off

**quiet 3-speed control & dimmer**

single pole fan control 1.5A (left) **S2-LFSQ-**  
 single pole dimmer 300W (right)  
 for use with only one ceiling paddle fan

**fully variable control & dimmer**

single pole fan control 2.5A (left) **S2-LF-**  
 single pole dimmer 300W (right)  
 for use with multiple ceiling paddle fans or exhaust fans

**replacement knobs**



- standard replacement knobs are available in white, ivory, almond, and light almond

**knobs**

single pole standard knob **SK-**  
 split knobs contact customer service