

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### SC40 4/0 Cubutt Splice

SC40
Nsi Industries
Standard Barrel Tinned Copper Splice 4/0 Awg: Standard Barrel Tinned Copper Splices Is A Type Of Copper Compression Connector That Is Produced From High Conductivity Copper Tubing. They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference. Listed For 35KV Maximum When Properly Installed.
0.0800 (lbs/each)
Large Terminals & Connectors
Copper
2
1
600 V
1 YEAR
Purple
Tin Plated
L=1.90 - OD=.690 - ID=.550
4/0 CUBUTT SPLICE
NSI SC-4/0 4/0 AWG Copper Short Bar
Standard Barrel Tinned Copper Splice 4/0 AWG: Standard Barrel Tinned Copper Splices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Standard Barrel Tinned Copper Splice 4/0 AWG: Standard Barrel Tinned Copper Splices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
4/0 Awg Copper Short Barrel Splice - Purple
4/0 AWG (STR) - CU Splice



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				<b>.</b>					_
ľ	۱ <i>۱</i>	12	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	<b>7</b>
	v			u	а	L.I	uı	<b>CI</b>	'In	H.V.	,, ,	па		u	

Brand	NSi
GTIN	00662381037091
Manufacturers Part Number	SC-4/0
UPC	662381037091

### **Taxonomies, Classifications, and Categories**

Category Description	Comp & Mech Lugs and Butt Splices
Type	Short Barrel - CU Splice

#### **Packaging**

,,,ag.,,g		
Carton	1	
Package	25	
Weight Per each	0.08	

### Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A
Temperature Rating	90 C