

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**Trade Size** 

Trade Size

## **SGB383CL 1" Diecast Mighty-Right Split Ground Bushing** *Nsi Industries*

Catalog Number	SGB383CL
Manufacturer	Nsi Industries
Description	Split Bushing, Insulated, Grounding, Zinc Die Cast, Size 1 Inch
Weight per unit	0.2170 (lbs/each)
Product Category	Aluminum
eatures	
Material	Zinc Alloy
media	Voc
Material, Color, and Finish	
Color	Grey with Black Insulator
Finish	Ball burnish
Dimensions and Weight	
Size	1
Descriptions	
Description Description	1" DIECAST MIGHTY-RIGHT SPLIT GROUND BUSHING
extra long description	BPT SGB-383CL 1" SPLT GND BSH LUG 4
Features	Split Bushings install after the wire pull. No more burning
	through bushings or fighting with pullers. Save time and effort
	too!
Long Description	Split Bushing, Insulated, Grounding, Zinc Die Cast, Size 1 Inch
Product Type	1" SPLT GND BSH Lug 4-14 Awg
Special Features	Grounding Lug Wire Capacity # 14 - #4
/lanufacturer Information	
Brand	Bridgeport Fittings
GTIN	00781747903839
Manufacturers Part Number	SGB-383CL
UPC	781747903839
axonomies, Classifications, and	Categories
Category Description	Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs
Туре	SPLIT

1



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

		^	•	^	$\sim$	-	•
_	a	-	ĸ	-	,		м
	"	۱.	•	•			

Carton	25	
Package	250	
Weight Per each	0.217	

## **Uses, Certifications, and Standards**

53, oci tilicationis, and standards	
Application	Used in situations where wires have already been pulled through Rigid/IMC conduit, and an insulated bushing is required. Grounding lug; aluminum alloy 6061-T6. Rated 150 Degree C. cULus listed. Patented. Now featuring UV Stabilized Insulators and Stainless Steel Hardware, perfect for solar and other outdoor installations!
standard	cULus
Temperature Rating	150?°C