


Specification grade GFCIs

Specification grade ground fault circuit interrupter receptacles

Product description

2-pole, 3-wire grounding
15A, 125V/AC; 20A, 125V/AC
NEMA 5-15, 5-20



5-15R

5-20R

Specification grade GFCIs



Rating			Description	Color suffix	Catalog no.			
A	V/AC	NEMA						
15	125	5-15R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, V, W	□ SGF15__	•		
			Duplex GFCI, mid-size wallplate, back & side wire	A, LA, V, W	□ SGF15__-M			
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	□ SGF15F__			
20	125	5-20R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, RD, V, W	□ SGF20__	•		
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	□ SGF20F__			

Includes standard size unbreakable wallplate unless otherwise noted
Consult factory customer service representative for additional packaging options

Specification grade combination GFCI receptacle & switch



Rating		NEMA	Description	Color suffix	Catalog no.
A	V/AC				
15	125	5-15R	GFCI receptacle with feed-through single-pole switch (rated 1800W @ 120V/AC, 60Hz)	A, LA, V, W	☐ SGFS15__-MSP


Specification grade blank face GFCI




Rating	A	V/AC	Description	Color suffix	Catalog no.
20	125		Blank face (dead front) GFCI, rated as 1.5HP motor control switch, back & side wire	A, BK, LA, V, W	□ SGFD20__

Accessories for GFCIs


Description	Color suffix	Catalog no.	
GFCI 7/8" extension ring, cULus Listed	BLK, LA, V, W	□ GFER__	•
Metal self-closing horizontal 1-Gang weather protective cover, decorator opening		□ S1966	• •
While-in-use metal weather protective standard depth 1-Gang cover, vertical mount		□ WIUMV-1	• •



SGF15



SGFS15



SGFD20



GFER



S1966



WIUMV-1



WIUMH-1

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

A	B	BK/BLK	GY	LA	RD	V	W
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

Specification information: Specification grade GFCI: H-18

Compliances, specifications and availability are subject to change without notice.

➔ ArrowLink option available. Add "MOD" suffix to standard catalog number (example SGF15W, SGF15WMOD). For ordering information on ArrowLink & ArrowLink SPD connectors, see Page H-4




RoHS compliant - Page Q-32

Specification grade GFCIs

Specification grade ground fault circuit interrupter receptacles

Product description

2-pole, 3-wire grounding
15A, 125V/AC; 20A, 125V/AC
NEMA 5-15, 5-20



5-15R

5-20R

Specification grade GFCIs



Rating		NEMA	Description	Color suffix	Catalog no.			
A	V/AC							
15	125	5-15R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, V, W	□ SGF15__	•		
			Duplex GFCI, mid-size wallplate, back & side wire	A, LA, V, W	□ SGF15__-M			
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	□ SGF15F__			
20	125	5-20R	Duplex GFCI, back & side wire	A, B, BK, GY, LA, RD, V, W	□ SGF20__	•		
			Duplex GFCI, back & side wire	B, BK, GY, LA, RD, V, W	□ SGF20F__			

Includes standard size unbreakable wallplate unless otherwise noted
Consult factory customer service representative for additional packaging options

Specification grade combination GFCI receptacle & switch



Rating		NEMA	Description	Color suffix	Catalog no.
A	V/AC				
15	125	5-15R	GFCI receptacle with feed-through single-pole switch (rated 1800W @ 120V/AC, 60Hz)	A, LA, V, W	☐ SGFS15__-MSP


Specification grade blank face GFCI




Rating	A	V/AC	Description	Color suffix	Catalog no.
20	125		Blank face (dead front) GFCI, rated as 1.5HP motor control switch, back & side wire	A, BK, LA, V, W	□ SGFD20__

Accessories for GFCIs


Description	Color suffix	Catalog no.	
GFCI 7/8" extension ring, cULus Listed	BLK, LA, V, W	□ GFER__	•
Metal self-closing horizontal 1-Gang weather protective cover, decorator opening		□ S1966	• •
While-in-use metal weather protective standard depth 1-Gang cover, vertical mount		□ WIUMV-1	• •



SGF15



SGFS15



SGFD20



GFER



S1966



WIUMV-1



WIUMH-1

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), RD (Red), V (Ivory), W (White)

A	B	BK/BLK	GY	LA	RD	V	W
(Almond)	(Brown)	(Black)	(Gray)	(Lt. Almond)	(Red)	(Ivory)	(White)

Specification information: Specification grade GFCI: H-18

Compliances, specifications and availability are subject to change without notice.

➔ ArrowLink option available. Add "MOD" suffix to standard catalog number (example SGF15W, SGF15WMOD). For ordering information on ArrowLink & ArrowLink SPD connectors, see Page H-4



RoHS compliant - Page Q-32