F.

G.

H.

	Indoor Enclosure		
	Model #	**Switch**	**Input Voltage**
	T171	SPST	125 VAC, 60Hz
	T172	SPST	208-277 VAC, 60Hz
	T173	DPST	125 VAC, 60Hz
	T174	DPST	208-277 VAC, 60Hz
	T175**	1NO/1NC	125 VAC, 60Hz
F.	**T176****	1NO/1NC	208-277 VAC, 60Hz
	Outdoor Enclosure		
	Model #	**Switch**	**Input Voltage**
	T173R	DPST	125 VAC, 60Hz
	T174R	DPST	208-277 VAC, 60Hz
G.	**T1471BR***	4PST	125 VAC, 60Hz
	T1472BR*	4PST	208-277 VAC, 60Hz
	T1475BR*	4PST	480 VAC, 60Hz
	T1871BR* †	2NO/2NC	125 VAC, 60Hz
H.	**T171CR**	SPST	125 VAC, 60Hz
	T173CR	DPST	125 VAC, 60Hz
	T174CR	DPST	208-277 VAC, 60Hz
	T1471BCR*	4PST	125 VAC, 60Hz

**Separate clock motor terminals for switching circuits not on line voltage*
***Can be wired as SPDT*
† Can be wired as DPDT

T170, T1400 and T1800 Series

24-Hour Time Switches with Skipper and Carryover

- For commercial, industrial and residential applications
- Controls loads up to 40 Amps per pole
- Direct 24-Hour control of most loads
- Up to 10 ON/OFF operations each day
- Minimum ON/OFF times of one hour
- Manual override
- One ON and one OFF tripper and three day-skipper screws

Models with Carryover (T171CR, T173CR, T174CR, T1471BCR)
- Minimum of 16 hours carryover operation
- Carryover automatically rewinds for one hour after power resumes
- 4PST models are ideal for 3-phase load control

Ratings:
Switch Ratings: 40 A Resistive each pole, 120-480 VAC, 40 A Inductive, Tungsten, 120, 240 or 277 VAC, 1000 VA Pilot Duty each pole, 120-277 VAC, 2 HP, (24 FLA), 120 VAC, 5 HP, (28 FLA), 240 VAC
4PST models also 7.5 HP (28 FLA) 208 VAC, 10 HP (28 FLA) 240 VAC 3-phase
Power Consumption: 3 W max.
Operating Temperature: -40ºF to 130ºF (-40ºC to 54ºC)
Warranty: 1 year

For additional trippers, see page 153; For additional skipper screws, see page 152; For replacement motors, see page 153

F.

G.

H.

	Indoor Enclosure		
	Model #	**Switch**	**Input Voltage**
	T171	SPST	125 VAC, 60Hz
	T172	SPST	208-277 VAC, 60Hz
	T173	DPST	125 VAC, 60Hz
	T174	DPST	208-277 VAC, 60Hz
	T175**	1NO/1NC	125 VAC, 60Hz
F.	**T176****	1NO/1NC	208-277 VAC, 60Hz
	Outdoor Enclosure		
	Model #	**Switch**	**Input Voltage**
	T173R	DPST	125 VAC, 60Hz
	T174R	DPST	208-277 VAC, 60Hz
G.	**T1471BR***	4PST	125 VAC, 60Hz
	T1472BR*	4PST	208-277 VAC, 60Hz
	T1475BR*	4PST	480 VAC, 60Hz
	T1871BR* †	2NO/2NC	125 VAC, 60Hz
H.	**T171CR**	SPST	125 VAC, 60Hz
	T173CR	DPST	125 VAC, 60Hz
	T174CR	DPST	208-277 VAC, 60Hz
	T1471BCR*	4PST	125 VAC, 60Hz

**Separate clock motor terminals for switching circuits not on line voltage*
***Can be wired as SPDT*
† Can be wired as DPDT

T170, T1400 and T1800 Series

24-Hour Time Switches with Skipper and Carryover

- For commercial, industrial and residential applications
- Controls loads up to 40 Amps per pole
- Direct 24-Hour control of most loads
- Up to 10 ON/OFF operations each day
- Minimum ON/OFF times of one hour
- Manual override
- One ON and one OFF tripper and three day-skipper screws

Models with Carryover (T171CR, T173CR, T174CR, T1471BCR)
- Minimum of 16 hours carryover operation
- Carryover automatically rewinds for one hour after power resumes
- 4PST models are ideal for 3-phase load control

Ratings:
Switch Ratings: 40 A Resistive each pole, 120-480 VAC, 40 A Inductive, Tungsten, 120, 240 or 277 VAC, 1000 VA Pilot Duty each pole, 120-277 VAC, 2 HP, (24 FLA), 120 VAC, 5 HP, (28 FLA), 240 VAC
4PST models also 7.5 HP (28 FLA) 208 VAC, 10 HP (28 FLA) 240 VAC 3-phase
Power Consumption: 3 W max.
Operating Temperature: -40ºF to 130ºF (-40ºC to 54ºC)
Warranty: 1 year

For additional trippers, see page 153; For additional skipper screws, see page 152; For replacement motors, see page 153