

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Size

TCF30 30A 600V Finger Safe Class J Fuse Bussmann Fuses

Catalog Number	TCF30
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series TCF Fuse, Bussmann Series Class CF Fuse, TCF, Time-Delay, Dual-Element Current Limiting Cube Fuse, 30 A, Indicating Fuse, Interrupting Rating Of 100 Ka At 300 VDC and 300 Ka At 600 Vac
Weight per unit	0.1100 (lbs/each)
Product Category	Tools & Testers
Features	
amperage rating	30
connection	Blade End
dimensions	1.8800 IN X 0.7500 IN X 1.0000 IN
element	Dual
Fuse Class	Class CF
interrupt rating	300 kAIC at 600 Vac100 kAIC at 300 Vdc
Material G	Glass Filled PES
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	

1.88 In Length X 0.75 In Height



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

11	es	r	rı	n	Ť١	\mathbf{n}	n	c
u	C.7	L		IJ	ш	w		_

Description	30A 600V FINGER SAFE CLASS J FUSE
extra long description	BUSS TCF30 TIME DELAY CUBEFUSE 30A
Features	The revolutionary BussmannTM series Low-PeakTM CUBEFuseTM delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful. And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann series TCF fuse, Bussmann Series Class CF fuse, TCF, time-delay, dual-element current limiting cube fuse, 30 A, indicating fuse, interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac
Product Type	Time Delay Cubefuse 30A Ind
Special Features	Finger Safe

Manufacturer Information

Brand	Eaton
GTIN	00051712615037
Manufacturers Part Number	TCF30
UPC	051712615037

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories	
Type	FUSE	
ckaging		

Packaging

Carton	12
Weight Per each	0.11

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security
	SystemsDatacenters - Facilities: Power DistributionCommercial /
	Institutional Buildings / Structures - Critical PowerInd Facilities &
	Factories - Facility: Power Distribution and ControlStationary
	Machinery and Equipment Outside Factory - HVAC
Mounting	35 mm DIN Rail, Chassis
standard	CSA Certified ,UL Listed,RoHS Compliant